



Safety Data Sheet
according to Regulation (EC)
No. 2015/830



SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	100635...	Revision Date:	09/12/2016
Product Name:	CARBOGUARD 635 - A	Supersedes Date:	23/11/2016
		Version Number:	1
1.2 Relevant identified uses of the substance or mixture and uses advised against	Base component of 2 components coating - Industrial use.		
Product to be mixed with:	CARBOGUARD 635 - B		
Mixing ratio by volume Part A/ Part B:	4 / 1		
1.3 Details of the supplier of the safety data sheet			
Importer:	StonCor Europe 9, Rue du Travail - 1400 Nivelles, Belgium		
Manufacturer:	Carboline Italia, S.p.a. Via Margherita Vigano' De Vizzi . n 77 20092 Cinisello Balsamo (MI) Italy		
	Regulatory / Technical Information: +32 67493710 Nivelles, Belgium +39 02253751 Cinisello Balsamo, Italy		
Datasheet Produced by:	Solvesi, Anna - ehs@stoncor.com		
1.4 Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US) PPC +1 412 6816669 (Outside US) Centro Antiveleni di Roma +39 06 49978000 (CAV Policlinico Umberto I - Roma)(24h/24h) Emergenza ambientale +39 335-601 32 88 / +39 347-949 84 88 / +39 348-246 90 99		

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Other EU extensions	EUH205
Flammable Liquid, category 3	H226
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Eye Irritation, category 2	H319

STOT, single exposure, category 3, NE	H336
STOT, repeated exposure, category 1	H372
Hazardous to the aquatic environment, Chronic, category 3	H412

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

crystalline cristobalite, poly(bisphenol a-co-epichlorohydrin), glycidyl end-capped, Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight <= 700)

HAZARD STATEMENTS

Other EU extensions	EUH205	Contains epoxy constituents. May produce an allergic reaction.
Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

PRECAUTION PHRASES

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.

ADDITIONAL INFORMATION

**	Note P : The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
----	---

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

SECTION 3: Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.	EINEC No.	Name According to EEC	%
14464-46-1	238-455-4	crystalline cristobalite	10-25

13463-67-7	236-675-5	titanium dioxide	10-25
25036-25-3	607-500-3	poly(bisphenol a-co-epichlorohydrin), glycidyl end-capped	10-25
14807-96-6	238-877-9	talc	2.5-10
25068-38-6	500-033-5	Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight <= 700)	2.5-10
	918-668-5	hydrocarbons, c9, aromatics**	2.5-10
1330-20-7	215-535-7	xylene	2.5-10
110-43-0	203-767-1	Heptan-2-one	2.5-10
100-41-4	202-849-4	Ethylbenzene	1.0-2.5
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom.**	0.1-1.0
108-88-3	203-625-9	Toluene	<0.1
108-05-4	203-545-4	Vinyl acetate	<0.1

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
14464-46-1		GHS08	H372	
13463-67-7	01-2119489379-17			
25036-25-3	polymer	GHS07	H315-317-319	
14807-96-6				
25068-38-6	01-2119456619-26	GHS07-GHS09	H315-317-319-411	
	01-2119455851-35	GHS02-GHS07-GHS08-GHS09	H226-304-335-336-411	
1330-20-7	01-2119488216-32	GHS02-GHS07-GHS08	H226-304-312-315-319-332-335-373	
110-43-0	01-2119902391-49	GHS02-GHS07	H226-302-332-336	
100-41-4	01-2119489370-35	GHS02-GHS07-GHS08	H225-304-332-373-412	
64742-95-6		GHS02-GHS07-GHS08-GHS09	H226-304-319-335-336-411	
108-88-3	01-2119471310-51	GHS02-GHS07-GHS08	H225-304-315-336-361d-373-412	
108-05-4		GHS02	H225	

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes. Irritating to skin. May cause sensitization by skin contact. Danger of serious damage to health by prolonged exposure. Prolonged or repeated exposure increases the risk.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Water spray/Dry powder/Alcohol-resistant foam/Carbon dioxide (CO₂) Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage**7.1 Precautions for safe handling**

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat. Extremes of temperature and direct sunlight.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure Controls/Personal Protection**8.1 Control parameters****Ingredients with Occupational Exposure Limits (UK WELS)**

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
crystalline cristobalite	14464-46-1				
titanium dioxide	13463-67-7			10 (total dust)	4 (resp. dust)
poly(bisphenol a-co-epichlorohydrin), glycidyl end-capped	25036-25-3				
talc	14807-96-6				1
Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6				
hydrocarbons, c9, aromatics**					100
xylene	1330-20-7	50	100	441	220
Heptan-2-one	110-43-0	50	100	475	237
Ethylbenzene	100-41-4	100	125	552	441
Solvent naphtha (petroleum), light arom.**	64742-95-6				100

Toluene	108-88-3	50	100	384	191
Vinyl acetate	108-05-4	5	10	35.2	17.6

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
crystalline cristobalite	14464-46-1	
titanium dioxide	13463-67-7	
poly(bisphenol a-co-epichlorohydrin), glycidyl end-capped	25036-25-3	
talc	14807-96-6	
Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	
hydrocarbons, c9, aromatics**		
xylene	1330-20-7	Sk
Heptan-2-one	110-43-0	
Ethylbenzene	100-41-4	Sk
Solvent naphtha (petroleum), light arom.**	64742-95-6	
Toluene	108-88-3	Sk
Vinyl acetate	108-05-4	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter. Wear respiratory protection with combination filter (dust and gas filter, EN 141) during spraying operations: Gas filter type A1 (organic substances). Dust filter P3 (for fine dust).

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron. Protective gloves complying with EN 374: Nitrile rubber. Butyl rubber.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Chemical Name:

titanium dioxide

EC No.:

236-675-5

CAS-No.:

13463-67-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							700 mg/kg/ bw/ day
Inhalation			10 mg/m ³				10 mg/m ³	
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	>1 mg/L
Fresh water sediments	1000 mg/kg
Marine water	0.127 mg/L
Marine sediments	100 mg/kg
Food chain	1667 mg/kg
Microorganisms in sewage treatment	100 mg/kg
soil (agricultural)	100 mg/kg d w
Air	

Chemical Name:

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

EC No.:

500-033-5

CAS-No.:

25068-38-6

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					0.75 mg/kg bw/day		0.75 mg/kg bw/ day
Inhalation		12.25 mg/m ³		12.25 mg/m ³				
Dermal		8.33 mg/kg bw/day		8.33 mg/kg bw/ day		3.571 mg/kg bw/day		3.571 mg/kg bw/ day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.006 mg/l
Fresh water sediments	
Marine water	0.0006 mg/l
Marine sediments	0.0996 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	0.196 mg/kg
Air	

Chemical Name:

hydrocarbons, c9, aromatics**

EC No.:

918-668-5

CAS-No.:**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							11 mg/kg bw/day
Inhalation				150 mg/m ³				32 mg/m ³
Dermal				25 mg/kg bw/day				11 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment soil (agricultural)	
Air	

Chemical Name:

xylene

EC No.:

215-535-7

CAS-No.:

1330-20-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.6 mg/kg bw/day
Inhalation	289 mg/m ³	289 mg/m ³		77 mg/m ³	174 mg/m ³	174 mg/m ³		14.8 mg/m ³
Dermal				180 mg/kg bw/day				108 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	6.58 mg/L
Air	2.31 mg/kg

Chemical Name:

Solvent naphtha (petroleum), light arom.**

EC No.:

265-199-0

CAS-No.:

64742-95-6

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required						11 mg/kg bw/day	
Inhalation				150 mg/m ³				32 mg/m ³
Dermal				25 mg/kg bw/day				11 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.635 mg/l
Fresh water sediments	3.29 mg/kg
Marine water	0.0635 mg/l
Marine sediments	0.329 mg/kg
Food chain	
Microorganisms in sewage treatment	100 mg/l
soil (agricultural)	0.29 mg/kg
Air	

Chemical Name:

Toluene

EC No.:

203-625-9

CAS-No.:

108-88-3

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							8.13 mg/kg bw/day
Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³	226 mg/m ³	226 mg/m ³	56.5 mg/m ³	56.5 mg/m ³
Dermal				384 mg/Kg bw/day				226 mg/Kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.68 mg/l
Fresh water sediments	16.39 mg/kg
Marine water	0.68 mg/l
Marine sediments	16.39 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	2.89 mg/kg
Air	

SECTION 9: Physical and Chemical Properties**9.1 Information on basic physical and chemical properties**

Appearance:	various colors
Physical State	LIQUID
Odor	epoxy
Odor threshold	Not determined
pH	N/A
Melting point / freezing point (°C)	Not determined

Boiling point/range (°C)	72 - 267
Flash Point, (°C)	26
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	Not determined
Vapour Pressure	N/D
Vapour density	Not determined
Relative density	1.74
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Not determined
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	296
Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.	
Specific Gravity (g/cm³)	1.74

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. StableRisk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat. Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available on the product itself as the product is not tested.

Inhalation LC50: No information available on the product itself as the product is not tested.

Irritation: Irritant

Corrosivity: No information available.

Sensitization:

May cause an allergic skin reaction.

Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	STOT RE
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
13463-67-7	titanium dioxide	>5000 mg/kg (oral-rat)	10000	
25036-25-3	poly(bisphenol a-co-epichlorohydrin), glycidyl end-capped	>2000 mg/kg (oral-rat)	>2000 mg/kg (dermal-rat)	
25068-38-6	Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight <= 700) hydrocarbons, c9, aromatics**	5000 mg/kg rat, oral	>2000 mg/kg dermal, rat M-F	
1330-20-7	xylene	>2000 mg/kg, rat, oral	> 3160 mg/kg, rabbit, dermal	> 6193 mg/m3
110-43-0	Heptan-2-one	1670 mg/kg rat oral	10206 mg/kg (dermal-rabbit)	20 mg/L (inh/vapour/rat)
100-41-4	Ethylbenzene	3500 mg/kg rat, oral		
64742-95-6	Solvent naphtha (petroleum), light arom.**	4700 mg/kg, oral, rat		3670 ppm/8 hours, rat, inhalation
108-88-3	Toluene	5000 mg/kg rat oral	14000 mg/kg rabbit	8000 ppm/4hrs, rat, inhalation

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
14464-46-1	crystalline cristobalite	No information	No information	
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)	16 mg/l (EC50, 72h, Pseudokirchnerella subcapitata)	>100 mg/l (EC50, 96h, Oncorhynchus Mykiss OECD203)
25036-25-3	poly(bisphenol a-co-epichlorohydrin), glycidyl end-capped	No information	No information	
14807-96-6	talca	No information	No information	
25068-38-6	Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight <= 700)	1.8mg/l (Daphnia magna, EC50, 48h,static)	11 mg/l (Scenedesmus capricornutum,EC50r, 72h)	1.5 mg/L (Rainbow trout), 3.6 mg/L (fish)
	hydrocarbons, c9, aromatics**	3,2 mg/l (Daphnia Magna)	No information	No information
1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/L (Selenastrum sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrochirus), 21.0 mg/L (Pimephales promelas)
110-43-0	Heptan-2-one	No information	No information	131 mg/L (Pimephales promelas)
100-41-4	Ethylbenzene	No information	No information	No information
64742-95-6	Solvent naphtha (petroleum), light arom.**	No information	2,6 mg/l(C50,72h Pseudokirchneriella subcapitata)	
108-88-3	Toluene	No information	No information	
108-05-4	Vinyl acetate	No information	No information	

Further Ecological Information

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

<u>CAS-No.</u>	<u>Name According to EEC</u>
25068-38-6	Reaction product: bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight <= 700) hydrocarbons, c9, aromatics**

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 08 01 11*
Packaging Waste Code: 15 01 10

SECTION 14: Transport Information

14.1	UN number	UN1263
14.2	UN proper shipping name	PAINT
	Technical name	Not applicable
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	Not applicable
14.4	Packing group	III
14.5	Environmental hazards	Marine Pollutant: NO
14.6	Special precautions for user	Not applicable
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

SECTION 15: Regulatory Information**15.1 Safety, health and environmental regulations/legislation for the substance or mixture:****National Regulations:**

Denmark Product Registration Number:	Not available
Danish MAL Code:	Not available
Danish MAL Code - Mixture:	Not available
Sweden Product Registration Number:	Not available
Norway Product Registration Number:	Not available
WGK Class:	2
Directive 2004/42/CE :	337 g/l (subcat j)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information**Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

01 - Product Information

Statement(s) Changed

Changes have been made to Section 3 of the Safety Data Sheet (SDS). Please refer to the Composition / Information on Ingredients in Section 3 of this SDS. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;
European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;
European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);
EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m ³	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.