

# Safety Data Sheet according to Regulation (EC) No. 2015/830



# SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

10063500 **Revision Date:** 1.1 Product Identifier 05/01/2017

Supercedes Date: 09/12/2016 CARBOGUARD 635 - B **Product Name:** 

Version Number:

1.2 Relevant identified uses of

the substance or mixture and uses advised against Hardener for 2 components coatings - Industrial use.

Product to be mixed with:

4/1

Mixing ratio by volume Part

A/Part B:

Details of the supplier of the safety data sheet

Importer: StonCor Europe

9, Rue du Travail - 1400 Nivelles, Belgium

Manufacturer: Carboline Italia, S.p.a.

Via Margherita Vigano' De Vizzi . n 77

20092 Cinisello Balsamo (MI)

CARBOGUARD 635 - A

Regulatory / Technical Information: +32 67493710 Nivelles, Belgium +39 02253751 Cinisello Balsamo, Italy

Solvesi, Anna - ehs@stoncor.com **Datasheet Produced by:** 

1.4 **Emergency telephone** 

number:

CHEMTREC +1 703 5273887 (Outside US)

PPC +1 412 6816669 (Outside US)

Centro Antiveleni di Roma +39 06 49978000 (CAV

Policlinico Umberto I - Roma)(24h/24h)

Emergenza ambientale +39 335-601 32 88 / +39

347-949 84 88 / +39 348-246 90 99

# **SECTION 2: Hazard Identification**

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

# **HAZARD STATEMENTS**

Flammable Liquid, category 3	H226
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Serious Eye Damage, category 1	H318
STOT, repeated exposure, category 1	H372
Hazardous to the aquatic environment, Chronic, category 3	H412

# 2.2 Label elements

# Symbol(s) of Product



# Signal Word

Danger

# Named Chemicals on Label

Butan-1-ol, 2,4,6-tris(dimethylaminomethyl)phenol, crystalline cristobalite

# **HAZARD STATEMENTS**

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P240	Ground/bond container and receiving equipment.
	P242	Use only non-sparking tools.
	P243	Take precautionary measures against static discharge.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P270	Do no eat, drink or smoke when using this product.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P302+P352	IF ON SKIN: Wash with plenty of water and soap.
	P305+P351+P33	IF IN EYES: Rinse cautiously with water for several minutes.
	8	Remove contact lenses, if present and easy to do so. Continue rinsing.
	P310	Immediately call a POISON CENTER or doctor/physician.
	P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
	P362	Take off contaminated clothing and wash before reuse.

ADDITIONAL INFORMATION

Note P: The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w

benzene

#### 2.3 Other hazards

No Information

#### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# SECTION 3: Composition/Information On Ingredients

#### 3.2 Mixtures

#### Hazardous Ingredients

CAS-No.	EINEC No.	Name According to EEC	<u>%</u>
14464-46-1	238-455-4	crystalline cristobalite	10-25
1330-20-7	215-535-7	xylene	10-25
71-36-3	200-751-6	Butan-1-ol	2.5-10
	918-668-5	hydrocarbons, c9, aromatics**	2.5-10
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	1.0-2.5
100-41-4	202-849-4	Ethylbenzene	0.1-1.0

<u>CAS-No.</u>	REACH Reg No.	CLP Symbols	CLP Hazard Statements	<u>M-Factors</u>
14464-46-1		GHS08	H372	
1330-20-7	01-2119488216-32	GHS02-GHS07-GHS08	H226-304-312-315-319-332-335-373	
71-36-3	01-2119484630-38	GHS02-GHS05-GHS07	H226-302-315-318-335-336	
	01-2119455851-35	GHS02-GHS07-GHS08-GHS09	H226-304-335-336-411	
90-72-2	01-2119560597-27	GHS05-GHS07	H302-314-317-412	
100-41-4	01-2119489370-35	GHS02-GHS07-GHS08	H225-304-332-373-412	

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

# **SECTION 4: First-aid Measures**

#### 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person.

#### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

# 4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. Risk of serious damage to eyes. May cause sensitization by skin contact. Danger of serious damage to health by prolonged exposure.

## 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# **SECTION 5: Fire-fighting Measures**

# 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

#### 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Water sprayDry powderAlcohol-resistant foamCarbon dioxide (CO2)Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

# **SECTION 6: Accidental Release Measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

# 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

# **SECTION 7: Handling and Storage**

# 7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat. Extremes of temperature and direct sunlight.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

No specific advice for end use available.

# **SECTION 8: Exposure Controls/Personal Protection**

# 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
crystalline cristobalite	14464-46-1				
xylene	1330-20-7	50	100	441	220
Butan-1-ol	71-36-3		50	154	
hydrocarbons, c9, aromatics**					100
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2				
Ethylbenzene	100-41-4	100	125	552	441

<u>Name</u>	CAS-No.	OEL Note
crystalline cristobalite	14464-46-1	
xylene	1330-20-7	Sk
Butan-1-ol	71-36-3	Sk
hydrocarbons, c9, aromatics**		
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	
Ethylbenzene	100-41-4	Sk

**FURTHER ADVICE**: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

# 8.2 Exposure controls

#### **Personal Protection**

**RESPIRATORY PROTECTION:** Respirator with a vapor filter. Wear respiratory protection with combination filter (dust and gas filter, EN 141) during spraying operations: Gas filter type A1 (organic substances). Dust filter P3 (for fine dust). **EYE PROTECTION:** Tightly fitting safety goggles.

**HAND PROTECTION:** Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

#### OTHER PROTECTIVE EQUIPMENT: No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Ensure adequate ventilation, especially in confined areas.

# **Chemical Name:**

xylene

**EC No.: CAS-No.:** 215-535-7 1330-20-7

# DNELs - Derived no effect level

		Wo	rkers			Cons	sumers	
Route of	Acute effect	Acute effects	Chronic effects	Chronic effects	Acute effect	Acute effects	Chronic effects	Chronic effects
Exposure	local	systemic	local	systemic	local	systemic	local	systemic
Oral		Not	required					1.6 mg/ kg bw/
								day
Inhalation	289 mg/ m³	289 mg/ m³		77 mg/ m³	174 mg/ m³	174 mg/ m³		14.8 mg/ m³
Demal				180 mg/ kg bw/				108 mg/ kg bw/
				day				day

# PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/ kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/ kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/ L
soil (agricultural)	2.31 mg/ kg
Air	

# **Chemical Name:**

Butan-1-ol

**EC No.: CAS-No.:** 200-751-6 71-36-3

# **DNELs - Derived no effect level**

	Workers				Cons	sumers		
Route of	Acute effect	Acute effects	Chronic effects	Chronic effects	Acute effect	Acute effects	Chronic effects	Chronic effects
Exposure	local	systemic	local	systemic	local	systemic	local	systemic
Oral	Not required						3,1 mg/ kg bw/	
								day
Inhalation	alation 310 mg/ m3					55 mg/ m3		
Demal								

# PNEC's - Predicted no effect concentration

Environmental protection target	PNEC				
Fresh water	0,082 mg/l				
Fresh water sediments 0,178 mg/ kg dw					
Marine water	0,0082 mg/l				
Marine sediments	0,0178 mg/ kg dw				
Food chain					
Microorganisms in sewage treatment					
soil (agricultural)	0,015 mg/ kg dw				
Air					

# **Chemical Name:**

hydrocarbons, c9, aromatics\*\*

EC No.: CAS-No.:

918-668-5

#### **DNELs - Derived no effect level**

	Workers				Cons	umers		
Route of	Acute effect	Acute effects	Chronic effects	Chronic effects	Acute effect	Acute effects	Chronic effects	Chronic effects
Exposure	local	systemic	local	systemic	local	systemic	local	systemic
Oral		Not	required					11 mg/ kg bw/
Inhalation				150 mg/ m3				32 mg/ m3
Dermal				25 mg/ kg bw/				11 mg/ kg bw/

# PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

## **Chemical Name:**

2,4,6-tris(dimethylaminomethyl)phenol

**EC No.: CAS-No.:** 202-013-9 90-72-2

# **DNELs - Derived no effect level**

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic effects	Chronic effects	Acute effect	Acute effects	Chronic effects	Chronic effects
Exposure	local	systemic	local	systemic	local	systemic	local	systemic
Oral	Not required							
Inhalation			4.9 mg/ m3	0.31 mg/m3				
Demal								

#### PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.084 mg/l
Fresh water sediments	
Marine water	0.0084 mg/l
Marine sediments	
Food chain	
Microorganisms in sewage treatment	0.2 mg/ l
soil (agricultural)	
Air	

# **SECTION 9: Physical and Chemical Properties**

9.1 Information on basic physical and chemical properties
Appearance: viscous liquid

Physical State LIQUID

Odor Amine

Odor threshold Not determined

pH N/A

Melting point / freezing point (°C) Not determined Boiling point/range (°C) 66 - 168 °C

Flash Point, (°C) 27

Evaporation rate Not determined Flammability (solid, gas) Not determined

Upper/lower flammability or

explosive limits

Not determined

Vapour Pressure N/D

Vapour density Not determined

Relative density 1.45
Solubility in / Miscibility with water N/D

Partition coefficient: n-octanol/water
Auto-ignition temperature (°C)

Not determined
Not determined
Not determined
Not determined
Viscosity

Solution temperature

Viscosity

Solution temperature

Not determined
Not determined
Not determined
Not determined

#### 9.2 Other information

VOC Content g/l: 296

Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.

Specific Gravity (g/cm3) 1.45

# **SECTION 10: Stability and Reactivity**

#### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

## 10.2 Chemical stability

Stable under recommended storage conditions. StableRisk of ignition.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Direct sources of heat. Extremes of temperature and direct sunlight.

# 10.5 Incompatible materials

Strong oxidizing agents.

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# **SECTION 11: Toxicological Information**

# 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: No information available on the product itself as the product is not tested.

Inhalation LC50: No information available on the product itself as the product is not tested.

Irritation: Irritant.

Corrosivity: No information available.

Sensitization: May cause an allergic skin reaction.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: STOT RE

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50
1330-20-7	xylene	>2000 mg/kg, rat, oral	3200 mg/ kg, rabbit, dermal	20 mg/L (inh/vapour/rat)
71-36-3	Butan-1-ol	790 mg/kg rat, oral	3400 mg/kg, rabbit	8000 mg/l 4hrs rat, inhalation
	hydrocarbons, c9, aromatics**	3592 mg/kg	> 3160 mg/ kg	> 6193 mg/ m3
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	2169 mg/kg oral, rat	2110 mg/kg rabbit	
100-41-4	Ethylbenzene	3500 mg/kg rat, oral		

#### Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.

# **SECTION 12: Ecological Information**

#### 12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

#### 12.6 Other adverse effects:

## No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
14464-46-1	crystalline cristobalite	No information	No information	
1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/ L (Selenastrum sp.)	2 - 11 mg/ L (Roccus saxatilis), 8.2 mg/ L (Salmo gairdneri), 13.5 mg/ L (Lepomis macrichirus), 21.0 mg/ L (Pimephales promelas)
71-36-3	Butan-1-ol	No information	No information	1740 mg/l (Pimephales promelas)
	hydrocarbons, c9, aromatics**	3,2 mg/ l (Daphnia Magna)	No information	No information
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	No information	84mg/I (EC50, 72h, Scendesmus subspicatus)	175 mg/L (LC50, 96h, Cyprinus carpio)
100-41-4	Ethylbenzene	No information	No information	No information

### **Further Ecological Information**

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

<u>CAS-No.</u> <u>Name According to EEC</u>

hydrocarbons, c9, aromatics\*\*

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

# **SECTION 13: Disposal Considerations**

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**European Waste Code:** 08 01 11\* **Packaging Waste Code:** 15 01 10

# **SECTION 14: Transport Information**

14.1 UN number UN126314.2 UN proper shipping name PAINT

Technical name Not applicable

14.3 Transport hazard class(es) 3

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards Marine Pollutant: NO

14.6 Special precautions for user Not applicable

EmS-No.: F-E, S-E

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable

the IBC code

# **SECTION 15: Regulatory Information**

# Safety, health and environmental regulations/legislation for the substance or mixture:

# **National Regulations:**

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

WGK Class: 2

**Directive 2004/42/CE**: 337 g/l (subcat j)

# 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# SECTION 16: Other Information

# Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

# Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

01 - Product Information

Statement(s) Changed

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation

#### (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

#### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit

STEL Short term exposure limit

OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable
LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road
RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is

not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.