



Safety Data Sheet
 according to Regulation (EC)
 No. 2015/830



SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	10089000	Revision Date:	22/02/2018
Product Name:	CARBOGUARD 890 - B	Supersedes Date:	02/12/2016
		Version Number:	1
1.2 Relevant identified uses of the substance or mixture and uses advised against	Hardener for 2 components coatings - Industrial use.		
Product to be mixed with:	CARBOGUARD 890 - A		
Mixing ratio by volume Part A/ Part B:	1 / 1		
1.3 Details of the supplier of the safety data sheet			
Importer:	StonCor Europe 9, Rue du Travail - 1400 Nivelles, Belgium		
Manufacturer:	Carboline Italia, S.p.a. Via Margherita Vigano' De Vizzi . n 77 20092 Cinisello Balsamo (MI) Italy		
	Regulatory / Technical Information: +32 67493710 Nivelles, Belgium +39 02253751 Cinisello Balsamo, Italy		
Datasheet Produced by:	Solvesi, Anna - ehs@stoncor.com		
1.4 Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US) PPC +1 412 6816669 (Outside US) Centro Antiveleni di Roma +39 06 49978000 (CAV Policlinico Umberto I - Roma)(24h/24h) Emergenza ambientale +39 335-601 32 88 / +39 347-949 84 88 / +39 348-246 90 99		

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 2	H225
Skin Corrosion, category 1B	H314-1B
Skin Sensitizer, category 1	H317
Acute Toxicity, Inhalation, category 4	H332
STOT, repeated exposure, category 1	H372

Hazardous to the aquatic environment, Chronic, category 3

H412

2.2 Label elements**Symbol(s) of Product****Signal Word**

Danger

Named Chemicals on Label

Benzyl alcohol, xylene, 3-Aminomethyl-3,5,5-trimethylcyclohexylamine, quartz (silicon dioxide), Cyclohexanemethanamine

HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Corrosion, category 1B	H314-1B	Causes severe skin burns and eye damage.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

PRECAUTION PHRASES

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.

ADDITIONAL INFORMATION

CAS 68609-08-5 REACH n° 01-2119965165-33 covered by cas 38294-64-3

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

SECTION 3: Composition/Information On Ingredients**3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>EINEC No.</u>	<u>Name According to EEC</u>	<u>%</u>
14808-60-7	238-878-4	quartz (silicon dioxide)	50-75
1330-20-7	215-535-7	xylene	2.5-10
100-51-6	202-859-9	Benzyl alcohol	2.5-10
2855-13-2	220-666-8	3-Aminomethyl-3,5,5-trimethylcyclohexylamine	2.5-10
67-63-0	200-661-7	Propan-2-ol	2.5-10
68609-08-5	614-657-1	Cyclohexanemethanamine	2.5-10
100-41-4	202-849-4	Ethylbenzene	1.0-2.5
68002-19-7	614-202-7	urea formaldehyde butilated	1.0-2.5
108-65-6	203-603-9	2-methoxy-1-methylethyl-acetate	1.0-2.5
71-36-3	200-751-6	Butan-1-ol	1.0-2.5

90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	0.1-1.0
9046-10-0		polyoxypropylenediamine	0.1-1.0

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
14808-60-7		GHS08	H372	
1330-20-7	01-2119488216-32	GHS02-GHS07-GHS08	H226-304-312-315-319-332-335-373	
100-51-6	01-2119492630-38	GHS07	H302-319-332	
2855-13-2	01-2119514687-32	GHS05-GHS07	H302-312-314-317-412	
67-63-0	01-2119457558-25	GHS02-GHS07	H225-319-336	
68609-08-5	01-2119965165-33	GHS05-GHS07-GHS09	H314-317-411	
100-41-4	01-2119489370-35	GHS02-GHS07-GHS08	H225-304-332-373-412	
68002-19-7			H413	
108-65-6	01-2119475791-29	GHS02	H226	
71-36-3	01-2119484630-38	GHS02-GHS05-GHS07	H226-302-315-318-335-336	
90-72-2	01-2119560597-27	GHS05-GHS07	H302-315-317-319-314-318	
9046-10-0	01-2119557899-12	GHS05	H314-412	

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes. Irritating to skin. May cause sensitization by skin contact. Danger of serious damage to health by prolonged exposure.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Water spray/Dry powder/Alcohol-resistant foam/Carbon dioxide (CO₂) Do not use a solid water stream as it may scatter and spread fire.

Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage**7.1 Precautions for safe handling**

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat. Extremes of temperature and direct sunlight.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection**8.1 Control parameters****Ingredients with Occupational Exposure Limits (UK WELS)**

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
quartz (silicon dioxide)	14808-60-7				0.1
xylene	1330-20-7	50	100	441	220
Benzyl alcohol	100-51-6				
3-Aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2				
Propan-2-ol	67-63-0	400	500	1250	999
Cyclohexanemethanamine	68609-08-5				
Ethylbenzene	100-41-4	100	125	552	441
urea formaldehyde butilated	68002-19-7				
2-methoxy-1-methylethyl-acetate	108-65-6	50	100	548	274
Butan-1-ol	71-36-3		50	154	
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2				
polyoxypropylenediamine	9046-10-0				

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
quartz (silicon dioxide)	14808-60-7	
xylene	1330-20-7	Sk
Benzyl alcohol	100-51-6	
3-Aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	
Propan-2-ol	67-63-0	

Cyclohexanemethanamine	68609-08-5	
Ethylbenzene	100-41-4	Can be absorbed through the skin.
urea formaldehyde butilated	68002-19-7	
2-methoxy-1-methylethyl-acetate	108-65-6	Sk
Butan-1-ol	71-36-3	Sk
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	
polyoxypropylenediamine	9046-10-0	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter. Wear respiratory protection with combination filter (dust and gas filter, EN 141) during spraying operations: Gas filter type A1 (organic substances). Dust filter P3 (for fine dust).

EYE PROTECTION: Tightly fitting safety goggles. Safety glasses with side-shields conforming to EN166.

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Chemical Name:

xylene

EC No.:
215-535-7

CAS-No.:
1330-20-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.6 mg/kg bw/day
Inhalation	289 mg/m ³	289 mg/m ³		77 mg/m ³	174 mg/m ³	174 mg/m ³		14.8 mg/m ³
Dermal				180 mg/kg bw/day				108 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/L
soil (agricultural)	2.31 mg/kg
Air	

Chemical Name:

Benzyl alcohol

EC No.:

202-859-9

CAS-No.:

100-51-6

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					25 mg/Kg bw/day		5 mg/Kg bw/day
Inhalation		110 mg/m ³		22 mg/m ³		40.55 mg/m ³		8.11 mg/m ³
Dermal		40 mg/kg bw/day		8 mg/kg bw/day		28.5 mg/Kg bw/day		5.7 mg/Kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	1 mg/l
Fresh water sediments	5.27 mg/Kg wwt
Marine water	0.1 mg/l
Marine sediments	0.527 mg/Kg wwt
Food chain	
Microorganisms in sewage treatment soil (agricultural)	39 mg/l
Air	0.456 mg/Kg wwt

Chemical Name:

3-Aminomethyl-3,5,5-trimethylcyclohexylamine

EC No.:

220-666-8

CAS-No.:

2855-13-2

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							
Inhalation	20.1	20.1						
Dermal								0.526 mg/kg bodyweight/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.06 mg/l
Fresh water sediments	5.784 mg/kg
Marine water	0.006mg/l
Marine sediments	0.578 mg/kg (dry weight)
Food chain	
Microorganisms in sewage treatment soil (agricultural)	1.121 mg/kg (dry weight)
Air	

Chemical Name:

Propan-2-ol

EC No.:

200-661-7

CAS-No.:

67-63-0

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required						26 mg/kg	
Inhalation				500 mg/m ³				89 mg/m ³
Dermal				888 mg/kg				319 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	140.9 mg/l
Fresh water sediments	552 mg/kg
Marine water	140.9 mg/l
Marine sediments	552 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	28 mg/kg
Air	

Chemical Name:

Ethylbenzene

EC No.:

202-849-4

CAS-No.:

100-41-4

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.6 mg/kg bw/day
Inhalation	293 mg/m ³ irritation (respiratory tract)	Low hazard (no threshold derived)		77 mg/m ³		Low hazard (no threshold derived)		15 mg/m ³
Dermal				180 mg/kg bw/day				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	100 µg/L
Fresh water sediments	13.7 mg/kg sediment dw
Marine water	10 - 100 µg/L
Marine sediments	1.37 mg/kg sediment dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	2.68 mg/kg soil dw
Air	

Chemical Name:

2-methoxy-1-methylethyl-acetate

EC No.:

203-603-9

CAS-No.:

108-65-6

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.67 mg/kg
Inhalation	550 mg/m ³			275 mg/m ³				33 mg/m ³
Dermal				153.5 mg/kg				54.8 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.635 mg/L
Fresh water sediments	3.29 mg/kg
Marine water	0.0635 mg/L
Marine sediments	0.329 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	100 mg/L
Air	0.29 mg/kg

Chemical Name:

Butan-1-ol

EC No.:

200-751-6

CAS-No.:

71-36-3

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							3,1 mg/kg bw/day
Inhalation			310 mg/m ³				55 mg/m ³	
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0,082 mg/l
Fresh water sediments	0,178 mg/kg dw
Marine water	0,0082 mg/l
Marine sediments	0,0178 mg/kg dw
Food chain	
Microorganisms in sewage treatment soil (agricultural)	0,015 mg/kg dw
Air	

Chemical Name:

2,4,6-tris(dimethylaminomethyl)phenol

EC No.:

202-013-9

CAS-No.:

90-72-2

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							
Inhalation			4.9 mg/m ³	0.31 mg/m ³				
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.084 mg/l
Fresh water sediments	
Marine water	0.0084 mg/l
Marine sediments	
Food chain	
Microorganisms in sewage treatment soil (agricultural)	0.2 mg/l
Air	

Chemical Name:

polyoxypropylenediamine

EC No.:**CAS-No.:**

9046-10-0

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							0.04 mg/kg bw/day
Inhalation								
Dermal			0.623 mg/cm ²	2.5 mg/kg bw/day			0.311 mg/cm ²	1.25 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.015 mg/l
Fresh water sediments	0.132 mg/kg
Marine water	0.0143 mg/l
Marine sediments	0.125 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	0.0176 mg/kg
Air	

SECTION 9: Physical and Chemical Properties**9.1 Information on basic physical and chemical properties**

Appearance:	Viscous Liquid
Physical State	LIQUID
Odor	Solvent
Odor threshold	Not determined
pH	N/A
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	80 - 260

Flash Point, (°C)	22
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	Not determined
Vapour Pressure	Not determined
Vapour density	Not determined
Relative density	Not determined
Solubility in / Miscibility with water	Not soluble
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Not determined
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	217
Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.	
Specific Gravity (g/cm³)	1.60

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. StableRisk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat. Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available on the product itself as the product is not tested.

Inhalation LC50: No information available on the product itself as the product is not tested.

Irritation: Irritant

Corrosivity: No information available.

Sensitization: May cause an allergic skin reaction.

Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	STOT RE 2
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1330-20-7	xylene	>2000 mg/kg, rat, oral	3200 mg/kg, rabbit, dermal	11 mg/L (ATE inh/vapour)
100-51-6	Benzyl alcohol	1620 mg/kg rat	2980 mg/kg, rabbit	
2855-13-2	3-Aminomethyl-3,5,5-trimethylcyclohexylamine	1030 mg/kg (oral-rat)	1840 mg/kg (dermal-rabbit)	
67-63-0	Propan-2-ol	4720 mg/kg rat, oral		22500 ppm/8hrs rat, inhalation
100-41-4	Ethylbenzene	3500 mg/kg rat, oral	>20000 mg/kg bw (rabbit)	
108-65-6	2-methoxy-1-methylethyl-acetate	8532 mg/kg, (oral, rat)	>5000 mg/kg (dermal, rat)	1105 mg/m ³ /4H
71-36-3	Butan-1-ol	790 mg/kg rat, oral	3400 mg/kg, rabbit	8000 mg/l 4hrs rat, inhalation
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	2169 mg/kg oral, rat	2110 mg/kg rabbit	
9046-10-0	polyoxypropylenediamine	2885 mg/kg, oral, rat	2980 mg/kg, rabbit	>74 mg/l , ratt

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
14808-60-7	quartz (silicon dioxide)	No information	No information	Not available

1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/L (Selenastrum sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrochirus), 21.0 mg/L (Pimephales promelas)
100-51-6	Benzyl alcohol	400 mg/L (daphnia magna)	700 mg/L (algae)	10 mg/L (fish)
2855-13-2	3-Aminomethyl-3,5,5-trimethylcyclohexylamine	23 mg/L	No information	110 mg/L
67-63-0	Propan-2-ol	No information	No information	4200 mg/L (fish)
68609-08-5	Cyclohexanemethanamine	No information	No information	Not available
100-41-4	Ethylbenzene	No information	No information	5.1 mg/L (Atlantic silverfish)
68002-19-7	urea formaldehyde butilated	No information	No information	Not available
108-65-6	2-methoxy-1-methylethyl-acetate	373 mg/l	No information	161 mg/L
71-36-3	Butan-1-ol	No information	No information	1740 mg/l (Pimephales promelas)
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	No information	84mg/l (EC50, 72h, Scendesmus subspicatus)	175 mg/L (LC50, 96h, Cyprinus carpio)
9046-10-0	polyoxypropylenediamine	418.34 mg/L	141.72 mg/L	Not available

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 08 01 11*
Packaging Waste Code: 15 01 10

SECTION 14: Transport Information

14.1	UN number	UN 3469
14.2	UN proper shipping name	PAINTS, FLAMMABLE, CORROSIVE
	Technical name	N/A
14.3	Transport hazard class(es)	3(8)
	Subsidiary shipping hazard	Not applicable
14.4	Packing group	II
14.5	Environmental hazards	Marine Pollutant: NO
14.6	Special precautions for user	Not applicable
	EmS-No.:	F-E, S-C
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:	Not available
Danish MAL Code:	Not available
Danish MAL Code - Mixture:	Not available
Sweden Product Registration Number:	Not available
Norway Product Registration Number:	Not available

Germany WGK Class:	2
Directive 2004/42/CE :	320 g/l (subcat j)
Covered by Directive 2012/18/EC (Seveso III):	P5c
Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:	Entry 3, 40

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

09 - Physical and Chemical Properties

15 - Regulatory Information

Revision Statement(s) Changed

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;
 European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;
 European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.