



Safety Data Sheet
according to Regulation (EC)
No. 2015/830



SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

| | | | |
|--|--|-------------------------|------------|
| 1.1 Product Identifier | 1455570S | Revision Date: | 05/07/2017 |
| Product Name: | PLASITE 4555 S - A | Supersedes Date: | 18/05/2015 |
| | | Version Number: | 1 |
| 1.2 Relevant identified uses of the substance or mixture and uses advised against | Base component of 2 components coating - Industrial use. | | |
| Product to be mixed with: | PLASITE 4555 S - B | | |
| Mixing ratio by volume Part A/ Part B: | 4 / 1 | | |
| 1.3 Details of the supplier of the safety data sheet | | | |
| Importer: | StonCor Europe 9, Rue du Travail - 1400 Nivelles, Belgium | | |
| Manufacturer: | Carboline Italia, S.p.a. Via Margherita Vigano' De Vizzi . n 77 20092 Cinisello Balsamo (MI) Italy | | |
| | Regulatory / Technical Information: +32 67493710 Nivelles, Belgium +39 02253751 Cinisello Balsamo, Italy | | |
| Datasheet Produced by: | Solvesi, Anna - ehs@stoncor.com | | |
| 1.4 Emergency telephone number: | CHEMTREC +1 703 5273887 (Outside US) PPC +1 412 6816669 (Outside US) Centro Antiveleni di Roma +39 06 49978000 (CAV Policlinico Umberto I - Roma)(24h/24h) Emergenza ambientale +39 335-601 32 88 / +39 347-949 84 88 / +39 348-246 90 99 | | |

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

| | |
|---|--------|
| Other EU extensions | EUH205 |
| Skin Irritation, category 2 | H315 |
| Skin Sensitizer, category 1 | H317 |
| Eye Irritation, category 2 | H319 |
| Hazardous to the aquatic environment, Chronic, category 2 | H411 |

2.2 Label elements

Symbol(s) of Product



Signal Word

Warning

Named Chemicals on Label

Epoxy resin based on bisphenol F, Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

HAZARD STATEMENTS

| | | |
|---|--------|--|
| Other EU extensions | EUH205 | Contains epoxy constituents. May produce an allergic reaction. |
| Skin Irritation, category 2 | H315 | Causes skin irritation. |
| Skin Sensitizer, category 1 | H317 | May cause an allergic skin reaction. |
| Eye Irritation, category 2 | H319 | Causes serious eye irritation. |
| Hazardous to the aquatic environment, Chronic, category 2 | H411 | Toxic to aquatic life with long lasting effects. |

PRECAUTION PHRASES

| | |
|-----------|--|
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P391 | Collect spillage. |

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

No information

SECTION 3: Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

| <u>CAS-No.</u> | <u>EINEC No.</u> | <u>Name According to EEC</u> | <u>%</u> |
|----------------|------------------|--|----------|
| 9003-36-5 | 500-006-8 | Epoxy resin based on bisphenol F | 50-75 |
| 12001-26-2 | 601-648-2 | mica | 10-25 |
| 68609-97-2 | 271-846-8 | Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 2.5-10 |
| 13463-67-7 | 236-675-5 | titanium dioxide | 2.5-10 |
| 112945-52-5 | 231-545-4 | silicon dioxide, crystalline-free | 1.0-2.5 |

| <u>CAS-No.</u> | <u>REACH Reg No.</u> | <u>CLP Symbols</u> | <u>CLP Hazard Statements</u> | <u>M-Factors</u> |
|----------------|----------------------|--------------------|------------------------------|------------------|
| 9003-36-5 | 01-2119454392-40 | GHS07-GHS09 | H315-317-411 | |
| 12001-26-2 | | GHS07 | H319-335 | |
| 68609-97-2 | 01-2119485289-22 | GHS07 | H315-317 | |
| 13463-67-7 | 01-2119489379-17 | | | |
| 112945-52-5 | 01-2119379499-16 | | | |

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: No Information

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (UK WELS)

| <u>Name</u> | <u>CAS-No.</u> | <u>LTEL ppm</u> | <u>STEL ppm</u> | <u>STEL mg/m3</u> | <u>LTEL mg/m3</u> |
|--|----------------|-----------------|-----------------|-------------------|-------------------|
| Epoxy resin based on bisphenol F | 9003-36-5 | | | | |
| mica | 12001-26-2 | | | 10 (total dust) | 0.8 (resp. dust) |
| Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 68609-97-2 | | | | |
| titanium dioxide | 13463-67-7 | | | 10 (total dust) | 4 (resp. dust) |
| silicon dioxide, crystalline-free | 112945-52-5 | | | 6 (Inh. dust) | 2.4 (Resp. dust) |

| <u>Name</u> | <u>CAS-No.</u> | <u>OEL Note</u> |
|--|----------------|-----------------|
| Epoxy resin based on bisphenol F | 9003-36-5 | |
| mica | 12001-26-2 | |
| Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 68609-97-2 | |
| titanium dioxide | 13463-67-7 | |
| silicon dioxide, crystalline-free | 112945-52-5 | |

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Protective gloves complying with EN 374. Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Chemical Name:

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

EC No.:

271-846-8

CAS-No.:

68609-97-2

DNELs - Derived no effect level

| Route of Exposure | Workers | | | | Consumers | | | |
|-------------------|--------------------|------------------------|-----------------------|--------------------------|--------------------|------------------------|-----------------------|--------------------------|
| | Acute effect local | Acute effects systemic | Chronic effects local | Chronic effects systemic | Acute effect local | Acute effects systemic | Chronic effects local | Chronic effects systemic |
| Oral | Not required | | | | | | | |
| Inhalation | | | | | | | | |
| Dermal | | | | | | | | |

PNEC's - Predicted no effect concentration

| Environmental protection target | PNEC |
|--|----------------|
| Fresh water | 0.0072 mg/l |
| Fresh water sediments | 66.77 mg/kg dw |
| Marine water | 0.00072 mg/l |
| Marine sediments | 6.677 mg/kg dw |
| Food chain | |
| Microorganisms in sewage treatment soil (agricultural) | |
| Air | |

Chemical Name:

titanium dioxide

EC No.:

236-675-5

CAS-No.:

13463-67-7

DNELs - Derived no effect level

| Route of Exposure | Workers | | | | Consumers | | | |
|-------------------|--------------------|------------------------|-----------------------|--------------------------|--------------------|------------------------|-----------------------|--------------------------|
| | Acute effect local | Acute effects systemic | Chronic effects local | Chronic effects systemic | Acute effect local | Acute effects systemic | Chronic effects local | Chronic effects systemic |
| Oral | Not required | | | | | | | 700 mg/kg/ bw/ day |
| Inhalation | | | 10 mg/m ³ | | | | 10 mg/m ³ | |
| Dermal | | | | | | | | |

PNEC's - Predicted no effect concentration

| Environmental protection target | PNEC |
|--|-------------------|
| Fresh water | 0.127 mg/L |
| Fresh water sediments | 1000 mg/kg dw |
| Marine water | 1 mg/L |
| Marine sediments | 100 mg/kg dw |
| Food chain | 1667 mg/kg (oral) |
| Microorganisms in sewage treatment soil (agricultural) | 100 mg/kg |
| Air | 100 mg/kg dw |

Chemical Name:

silicon dioxide, crystalline-free

EC No.:

231-545-4

CAS-No.:

112945-52-5

DNELs - Derived no effect level

| Route of Exposure | Workers | | | | Consumers | | | |
|-------------------|--------------------|------------------------|-----------------------|--------------------------|--------------------|------------------------|-----------------------|--------------------------|
| | Acute effect local | Acute effects systemic | Chronic effects local | Chronic effects systemic | Acute effect local | Acute effects systemic | Chronic effects local | Chronic effects systemic |
| Oral | Not required | | | | | | | |
| Inhalation | | | | 4 mg/m ³ | | | | |
| Dermal | | | | | | | | |

PNEC's - Predicted no effect concentration

| Environmental protection target | PNEC |
|------------------------------------|------|
| Fresh water | |
| Fresh water sediments | |
| Marine water | |
| Marine sediments | |
| Food chain | |
| Microorganisms in sewage treatment | |
| soil (agricultural) | |
| Air | |

SECTION 9: Physical and Chemical Properties

| | |
|--|----------------|
| 9.1 Information on basic physical and chemical properties | |
| Appearance: | VISCOUS LIQUID |
| Physical State | LIQUID |
| Odor | epoxy |
| Odor threshold | Not determined |
| pH | N/A |
| Melting point / freezing point (°C) | Not determined |
| Boiling point/range (°C) | N.A. - 200 |
| Flash Point, (°C) | 149 |
| Evaporation rate | Not determined |
| Flammability (solid, gas) | Not determined |
| Upper/lower flammability or explosive limits | 3.8 - 21.0 |
| Vapour Pressure | N/D |
| Vapour density | Not determined |
| Relative density | Not determined |
| Solubility in / Miscibility with water | Not determined |
| Partition coefficient: n-octanol/water | Not determined |
| Auto-ignition temperature (°C) | Not determined |
| Decomposition temperature (°C) | Not determined |
| Viscosity | Not determined |
| Explosive properties | Not determined |
| Oxidising properties | Not determined |

9.2 Other information

| | |
|--|------|
| VOC Content g/l: | 0 |
| Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2. | |
| Specific Gravity (g/cm ³) | 1.33 |

SECTION 10: Stability and Reactivity**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed. Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

No Information

10.5 Incompatible materials

Strong oxidizing agents. Acids and bases. Amines.

10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

SECTION 11: Toxicological Information**11.1 Information on toxicological effects****Acute Toxicity:**

| | |
|------------------|----------------|
| Oral LD50: | No Information |
| Inhalation LC50: | No Information |

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Name According to EEC</u> | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|----------------------------------|-------------------------|---------------------------|-------------------|
| 9003-36-5 | Epoxy resin based on bisphenol F | >5000 mg/Kg (rat, oral) | >2000 mg/Kg (rat, dermal) | |
| 12001-26-2 | mica | > 5000 mg/kg (rat) | | |

| | | | |
|-------------|--|------------------------|----------------------------|
| 68609-97-2 | Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 17100 mg/kg, oral, rat | 4500 mg/kg, dermal, rabbit |
| 13463-67-7 | titanium dioxide | >5000 mg/kg (oral-rat) | 10000 |
| 112945-52-5 | silicon dioxide, crystalline-free | 10000 mg/kg, oral, rat | |

Additional Information:

This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12: Ecological Information**12.1 Toxicity:**

| | |
|-----------------------------|----------------|
| EC50 48hr (Daphnia): | No information |
| IC50 72hr (Algae): | No information |
| LC50 96hr (fish): | No information |

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: No information

12.6 Other adverse effects: No information

| <u>CAS-No.</u> | <u>Name According to EEC</u> | <u>EC50 48hr</u> | <u>IC50 72hr</u> | <u>LC50 96hr</u> |
|----------------|--|--|---|---|
| 9003-36-5 | Epoxy resin based on bisphenol F | No information | 1.8 mg/l (algae, EC50 static) | 0.55 mg/l (fish) |
| 12001-26-2 | mica | No information | No information | |
| 68609-97-2 | Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | No information | No information | > 5.000 mg/l (Oncorhynchus mykiss, CL50, 96h static), |
| 13463-67-7 | titanium dioxide | >100 mg/l (EC50, 48h, Daphnia magna OECD202) | 16 mg/l (EC50, 72h, Pseudokirchnerella subcapitata) | >100 mg/l (EC50, 96h, Oncorhynchus Mykiss OECD203) |
| 112945-52-5 | silicon dioxide, crystalline-free | No information | No information | > 10.000 mg/l (LC50,96h,Brachydanio rerio) |

Further Ecological Information

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

| <u>CAS-No.</u> | <u>Name According to EEC</u> |
|----------------|----------------------------------|
| 9003-36-5 | Epoxy resin based on bisphenol F |

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

| | |
|------------------------------|---------|
| European Waste Code: | 080111* |
| Packaging Waste Code: | 150110 |

SECTION 14: Transport Information

| | | |
|------|--|--|
| 14.1 | UN number | UN 3082 |
| 14.2 | UN proper shipping name | . Environmentally Hazardous Substance, Liquid, N.O.S. (Epoxy resin based on bisphenol F) |
| | Technical name | Not applicable |
| 14.3 | Transport hazard class(es) | 9 |
| | Subsidiary shipping hazard | Not applicable |
| 14.4 | Packing group | III |
| 14.5 | Environmental hazards | Marine Pollutant: YES (epoxy resin based on bisphenol F) |
| 14.6 | Special precautions for user | Not applicable |
| | EmS-No.: | F-A, S-F |
| 14.7 | Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code | Not applicable |

SECTION 15: Regulatory Information**15.1 Safety, health and environmental regulations/legislation for the substance or mixture:****National Regulations:**

| | |
|--|------------------|
| Denmark Product Registration Number: | Not available |
| Danish MAL Code: | Not available |
| Danish MAL Code - Mixture: | Not available |
| Sweden Product Registration Number: | Not available |
| Norway Product Registration Number: | Not available |
| WGK Class: | 2 |
| Directive 2004/42/CE : | 0 g/l (subcat j) |
| Covered by Directive 2012/18/EC (Seveso III): | E2 |
| Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006: | Mix: point 3 |

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information**Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

| | |
|------|--|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

09 - Physical and Chemical Properties

13 - Disposal Information

14 - Transportation Information

15 - Regulatory Information

Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;
European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);
EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

| | |
|--------|---|
| CLP | Classification, Labeling & Packaging Regulation |
| EC | European Commission |
| EU | European Union |
| US | United States |
| CAS | Chemical Abstract Service |
| EINECS | European Inventory of Existing Chemical Substances |
| REACH | Registration, Evaluation, Authorization of Chemicals Regulation |
| GHS | Globally Harmonized System of Classification and Labeling of Chemicals |
| LTEL | Long term exposure limit |
| STEL | Short term exposure limit |
| OEL | Occupational exposure limit |
| ppm | Parts per million |
| mg/m3 | Milligrams per cubic meter |
| TLV | Threshold Limit Value |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| OSHA | Occupational Safety & Health Administration |
| PEL | Permissible Exposure Limits |
| VOC | Volatile organic compounds |
| g/l | Grams per liter |
| mg/kg | Milligrams per kilogram |
| N/A | Not applicable |
| LD50 | Lethal dose at 50% |
| LC50 | Lethal concentration at 50% |
| EC50 | Half maximal effective concentration |
| IC50 | Half maximal inhibitory concentration |
| PBT | Persistent bioaccumulative toxic chemical |
| vPvB | Very persistent and very bioaccumulative |
| EEC | European Economic Community |
| ADR | International Transport of Dangerous Goods by Road |
| RID | International Transport of Dangerous Goods by Rail |
| UN | United Nations |
| IMDG | International Maritime Dangerous Goods Code |
| IATA | International Air Transport Association |
| MARPOL | International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978 |
| IBC | International Bulk Container |
| RTI | Respiratory Tract Irritation |
| NE | Narcotic Effects |

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.