



**Safety Data Sheet**  
 according to Regulation (EC)  
 No. 2015/830



**SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking**

<b>1.1 Product Identifier</b>	14674900	<b>Revision Date:</b>	22/06/2017
<b>Product Name:</b>	THERMALINE 4674 BLACK	<b>Supersedes Date:</b>	04/06/2015
		<b>Version Number:</b>	1
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b>	Monocomponent industrial coating - Industrial use.		
<b>Product to be mixed with:</b>	N/A		
<b>Mixing ratio by volume Part A/ Part B:</b>	N/A		
<b>1.3 Details of the supplier of the safety data sheet</b>			
<b>Importer:</b>	StonCor Europe 9, Rue du Travail - 1400 Nivelles, Belgium		
<b>Manufacturer:</b>	Carboline Italia, S.p.a. Via Margherita Vigano' De Vizzi . n 77 20092 Cinisello Balsamo (MI) Italy		
	Regulatory / Technical Information: +32 67493710 Nivelles, Belgium +39 02253751 Cinisello Balsamo, Italy		
<b>Datasheet Produced by:</b>	Solvesi, Anna - ehs@stoncor.com		
<b>1.4 Emergency telephone number:</b>	CHEMTREC +1 703 5273887 (Outside US) PPC +1 412 6816669 (Outside US) Centro Antiveleni di Roma +39 06 49978000 (CAV Policlinico Umberto I - Roma)(24h/24h) Emergenza ambientale +39 335-601 32 88 / +39 347-949 84 88 / +39 348-246 90 99		

**SECTION 2: Hazard Identification**

**2.1 Classification of the substance or mixture**

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

**HAZARD STATEMENTS**

Flammable Liquid, category 3	H226
Aspiration Hazard, category 1	H304
Skin Irritation, category 2	H315
Eye Irritation, category 2	H319
Acute Toxicity, Inhalation, category 4	H332

STOT, single exposure, category 3, RTI  
STOT, repeated exposure, category 2

H335  
H373

## 2.2 Label elements

### Symbol(s) of Product



### Signal Word

Danger

### Named Chemicals on Label

2-methylpropan-1-ol, Ethylbenzene, Toluene, xylene

#### HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Aspiration Hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.

#### PRECAUTION PHRASES

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

#### ADDITIONAL INFORMATION

Xylene Note C: mixture of isomers.

### 2.3 Other hazards

No Information

#### Results of PBT and vPvB assessment:

No information

## SECTION 3: Composition/Information On Ingredients

### 3.2 Mixtures

#### Hazardous Ingredients

CAS-No.	EINEC No.	Name According to EEC	%
1330-20-7	215-535-7	xylene	25-50
100-41-4	202-849-4	Ethylbenzene	10-25
14807-96-6	238-877-9	talc	2.5-10
78-83-1	201-148-0	2-methylpropan-1-ol	0.1-1.0
108-88-3	203-625-9	Toluene	0.1-1.0

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
1330-20-7	01-2119488216-32	GHS02-GHS07-GHS08	H226-304-312-315-319-332-335-373	
100-41-4	01-2119489370-35	GHS02-GHS07-GHS08	H225-304-332-373-412	
14807-96-6				
78-83-1	01-2119484609-23	GHS02-GHS05-GHS07	H226-315-318-335-336	
108-88-3	01-2119471310-51	GHS02-GHS07-GHS08	H225-304-315-336-361d-373-412	

**Additional Information:** The text for CLP Hazard Statements shown above (if any) is given in Section 16.

## SECTION 4: First-aid Measures

### 4.1 Description of First Aid Measures

**GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice.

**AFTER INHALATION:** Move to fresh air.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

No Information

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

## SECTION 5: Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

### 5.2 Special hazards arising from the substance or mixture

No Information

### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

## SECTION 6: Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## SECTION 7: Handling and Storage

### 7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Direct sources of heat.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

No specific advice for end use available.

## SECTION 8: Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
xylene	1330-20-7	50	100	441	220
Ethylbenzene	100-41-4	100	125	552	441
talc	14807-96-6				1
2-methylpropan-1-ol	78-83-1	50	75	231	154
Toluene	108-88-3	50	100	384	191

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
xylene	1330-20-7	Sk
Ethylbenzene	100-41-4	Sk
talc	14807-96-6	
2-methylpropan-1-ol	78-83-1	
Toluene	108-88-3	Sk

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** Respirator with combination filter for vapour/particulate (EN 141).

**EYE PROTECTION:** Tightly fitting safety goggles.

**HAND PROTECTION:** Rubber or plastic gloves. Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

**Chemical Name:**

xylene

**EC No.:**

215-535-7

**CAS-No.:**

1330-20-7

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.6 mg/kg bw/day
Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>		77 mg/m <sup>3</sup>	174 mg/m <sup>3</sup>	174 mg/m <sup>3</sup>		14.8 mg/m <sup>3</sup>
Dermal				180 mg/kg bw/day				108 mg/kg bw/day

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	6.58 mg/L
Air	2.31 mg/kg

**Chemical Name:**

Ethylbenzene

**EC No.:**

202-849-4

**CAS-No.:**

100-41-4

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.6 mg/kg bw/day
Inhalation	293 mg/m <sup>3</sup> irritation (respiratory tract)	Low hazard (no threshold derived)		77 mg/m <sup>3</sup>		Low hazard (no threshold derived)		15 mg/m <sup>3</sup>
Dermal				180 mg/kg bw/day				

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	100 µg/L
Fresh water sediments	13.7 mg/kg sediment dw
Marine water	10 - 100 µg/L
Marine sediments	1.37 mg/kg sediment dw
Food chain	
Microorganisms in sewage treatment soil (agricultural)	2.68 mg/kg soil dw
Air	

**Chemical Name:**

2-methylpropan-1-ol

**EC No.:**

201-148-0

**CAS-No.:**

78-83-1

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							25 mg/kg
Inhalation			310 mg/m3				55 mg/m3	
Dermal								

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	0,4 mg/l
Fresh water sediments	1,52 mg/kg
Marine water	0,04 mg/l
Marine sediments	0,152 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	10 mg/l
Air	0,0699 mg/kg

**Chemical Name:**

Toluene

**EC No.:**

203-625-9

**CAS-No.:**

108-88-3

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							8.13 mg/kg bw/day
Inhalation	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3	226 mg/m3	226 mg/m3	56.5 mg/m3	56.5 mg/m3
Dermal				384 mg/Kg bw/day				226 mg/Kg bw/day

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	0.68 mg/l
Fresh water sediments	16.39 mg/kg
Marine water	0.68 mg/l
Marine sediments	16.39 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	13.61 mg/l
Air	2.89 mg/kg

**SECTION 9: Physical and Chemical Properties****9.1 Information on basic physical and chemical properties**

<b>Appearance:</b>	Black
<b>Physical State</b>	Liquid
<b>Odor</b>	Solvent
<b>Odor threshold</b>	Not determined
<b>pH</b>	N/A
<b>Melting point / freezing point (°C)</b>	Not determined
<b>Boiling point/range (°C)</b>	>35 - N.D.

<b>Flash Point, (°C)</b>	27
<b>Evaporation rate</b>	Not determined
<b>Flammability (solid, gas)</b>	Not determined
<b>Upper/lower flammability or explosive limits</b>	Not determined
<b>Vapour Pressure</b>	n/d
<b>Vapour density</b>	Not determined
<b>Relative density</b>	Not determined
<b>Solubility in / Miscibility with water</b>	n/d
<b>Partition coefficient: n-octanol/water</b>	Not determined
<b>Auto-ignition temperature (°C)</b>	Not determined
<b>Decomposition temperature (°C)</b>	Not determined
<b>Viscosity</b>	Not determined
<b>Explosive properties</b>	Not determined
<b>Oxidising properties</b>	Not determined

**9.2 Other information**

<b>VOC Content g/l:</b>	500
<b>Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.</b>	
<b>Specific Gravity (g/cm<sup>3</sup>)</b>	1.07

## SECTION 10: Stability and Reactivity

**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

**10.2 Chemical stability**

Stable under recommended storage conditions. Risk of ignition.

**10.3 Possibility of hazardous reactions**

No Information

**10.4 Conditions to avoid**

Direct sources of heat.

**10.5 Incompatible materials**

Strong oxidizing agents.

**10.6 Hazardous decomposition products**

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## SECTION 11: Toxicological Information

**11.1 Information on toxicological effects****Acute Toxicity:**

**Oral LD50:** No Information

**Inhalation LC50:** No Information

**Irritation:** No information available.

**Corrosivity:** No information available.

**Sensitization:** No information available.

<b>Repeated dose toxicity:</b>	No information available.
<b>Carcinogenicity:</b>	No information available.
<b>Mutagenicity:</b>	No information available.
<b>Toxicity for reproduction:</b>	No information available.
<b>STOT-single exposure:</b>	No information available.
<b>STOT-repeated exposure:</b>	No information available.
<b>Aspiration hazard:</b>	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.  
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1330-20-7	xylene	>2000 mg/kg, rat, oral	3200 mg/kg, rabbit, dermal	20 mg/L (inh/vapour/rat)
100-41-4	Ethylbenzene	3500 mg/kg rat, oral	>20000 mg/kg bw (rabbit)	
78-83-1	2-methylpropan-1-ol	2830 - 3350 mg/kg (oral-rat)	> 2000 mg/kg (dermal - rabbit)	> 20 mg/L (Inhalation, rat, 6h)
108-88-3	Toluene	5000 mg/kg rat oral	14000 mg/kg rabbit	8000 ppm/4hrs, rat, inhalation

#### Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.

## SECTION 12: Ecological Information

### 12.1 Toxicity:

<b>EC50 48hr (Daphnia):</b>	No information
<b>IC50 72hr (Algae):</b>	No information
<b>LC50 96hr (fish):</b>	No information

**12.2 Persistence and degradability:** No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

**12.5 Results of PBT and vPvB assessment:** No information

**12.6 Other adverse effects:** No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/L (Selenastrum sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrochirus), 21.0 mg/L (Pimephales promelas)
100-41-4	Ethylbenzene	No information	No information	5.1 mg/L (Atlantic silverfish)
14807-96-6	talc	No information	No information	
78-83-1	2-methylpropan-1-ol	1100 mg/L (Daphnia magna)	1799 mg/L (Scenedesmus subspicatus)	1430 mg/L (Pimephales promelas)
108-88-3	Toluene	No information	No information	5.5 mg/l (Oncorhynchus kisutch)



**SECTION 13: Disposal Considerations**

**13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**European Waste Code:** 080111\*  
**Packaging Waste Code:** 150110

**SECTION 14: Transport Information**

<b>14.1 UN number</b>	UN 1263
<b>14.2 UN proper shipping name</b>	.PAINT
<b>Technical name</b>	Not applicable
<b>14.3 Transport hazard class(es)</b>	3
<b>Subsidiary shipping hazard</b>	Not applicable
<b>14.4 Packing group</b>	III
<b>14.5 Environmental hazards</b>	Marine Pollutant: NO
<b>14.6 Special precautions for user</b>	Not applicable
<b>EmS-No.:</b>	F-E , S-E
<b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code</b>	Not applicable

**SECTION 15: Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation for the substance or mixture:**

**National Regulations:**

<b>Denmark Product Registration Number:</b>	Not available
<b>Danish MAL Code:</b>	Not available
<b>Danish MAL Code - Mixture:</b>	Not available
<b>Sweden Product Registration Number:</b>	Not available
<b>Norway Product Registration Number:</b>	Not available
<b>WGK Class:</b>	2
<b>Directive 2004/42/CE :</b>	500 g/l (subcat i)
<b>Covered by Directive 2012/18/EC (Seveso III):</b>	P5c
<b>Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:</b>	CAS 108-88-3, point 48; Mix: 3-40

**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**SECTION 16: Other Information**

**Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Reasons for revision**

Regulatory Formula Source Changed

Composition Information Changed

Substance and/or Product Properties Changed in Section(s) :

09 - Physical and Chemical Properties

13 - Disposal Information

14 - Transportation Information

15 - Regulatory Information

Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

## List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;

European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);

EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

## Acronym &amp; Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m <sup>3</sup>	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community

ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

