



Safety Data Sheet
according to Regulation (EC)
No. 453/2010



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	TROMEK00	Revision Date:	26/05/2015
Product Name:	THINNER MEK	Supersedes Date:	26/05/2015
CAS Number:	78-93-3		
EC Number:	201-159-0		
Index Number:	606-002-00-3		
REACH Reg No.	01-2119457290-43		
Sector of Use Code:			
1.2 Relevant identified uses of the substance or mixture and uses advised against	Thinner for industrial coatings - Industrial use		
1.3 Details of the supplier of the safety data sheet			
Importer:	StonCor Europe 9 Rue du Travail, 1400 Nivelles, Belgium		
Manufacturer:	StonCor Europe 9 Rue du Travail 1400 Nivelles Belgium		
	Regulatory / Technical Information: +32 67493710 Nivelles, Belgium +39 02253751 Cologno Monzese, Italy		
Datasheet Produced by:	Diepstraten, Guus - ehs@stoncor.com		
1.4 Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US)		

2 Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Skin drying or cracking	EUH066
Flammable Liquid, category 2	H225
Eye Irritation, category 2	H319
STOT, single exposure, category 3, NE	H336

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

butanone

HAZARD STATEMENTS

Skin drying or cracking	E UH066	Repeated exposure may cause skin dryness or cracking.
Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.

PRECAUTION PHRASES

P210	Keep away from heat/sparks/open flames/hot surfaces. –No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Not applicable

Results of PBT and vPvB assessment

No information

3. Composition/Information On Ingredients

3.1 Substances

Hazardous Ingredients

<u>CAS-No.</u>	<u>EINEC No.</u>	<u>Name According to EEC</u>	<u>%</u>
78-93-3	201-159-0	butanone	75-100

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
78-93-3	01-2119457290-43	GHS02-GHS07	H225-319-336	

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove

contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(EU)

Name	%	LTEL ppm	STEL ppm	STEL mg/m ³	LTEL mg/m ³	OEL Note
butanone	75-100	200	300	900	600	Sk

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified at the EU level under the dangerous substances and preparations regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Chemical Name:

butanone

EC No.:

201-159-0

CAS-No.:

78-93-3

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							31 mg/kg
Inhalation				600 mg/m ³				106 mg/m ³
Dermal				1161 mg/kg				412 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	55.8 mg/l
Fresh water sediments	284.74 mg/kg
Marine water	
Marine sediments	284.7 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	22.5 mg/kg
Air	

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Liquid
Physical State	LIQUID
Odor	SOLVENT
Odor threshold	Not determined
pH	N/A
Melting point / freezing point (°C)	-86,3°C
Boiling point/range (°C)	80°C - N.D.

Flash Point, (°C)	-4
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	1,8 Vol% - 11,5 Vol%
Vapour Pressure	105 hPa
Vapour density	NOT DETERMINED
Relative density	Not determined
Solubility in /Miscibility with water	290 g/l Slightly soluble
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	514°C
Decomposition temperature (°C)	Not determined
Viscosity	1 mPas (20°C)
Explosive properties	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	810
Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2	
Specific Gravity (g/cm³)	0.81

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD₅₀:

Inhalation LC₅₀:

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below.

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
78-93-3	butanone	2737 mg/kg rat oral	6480 mg/kg (dermal-rabbit)	5000 ppm/1 hour rat inhalation

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: No information

12.6 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
78-93-3	butanone	5091 mg/L	No information	3.22 mg/L (Lepomis macrochirus)

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 07 01 04
Packaging Waste Code: 150110

14. Transport Information

14.1	UN number	1193
14.2	UN proper shipping name	ETHYL METHYL KETONE (METHYL ETHYL KETONE)
	Technical name	ETHYL METHYL KETONE (METHYL ETHYL KETONE)
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	
14.4	Packing group	II
14.5	Environmental hazards	Marine Pollutant: No
14.6	Special precautions for user	
	EmS-No.:	F-E,S-D
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:

Danish MAL Code:

Sweden Product Registration Number:

Norway Product Registration Number:

WGK Class: 1

Chemical Safety Assessment

15.2 No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark
ESIS (The European Chemical Substances Information System), provided by the European Commission
Joint Research Centre in Ispra, Italy
Annex VI of the EU Council Directive 67/548/EEC
Council Directive 67/548/EEC - Annex I or EU Council Directive 1999/45/EC
European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation)
EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.