



**Safety Data Sheet**  
**according to Regulation (EC)**  
**No. 453/2010**

## 1. Identification of the Substance/Mixture and the Company/Undertaking

<b>1.1 Product Identifier</b>	52609/B	<b>Revision Date:</b>	02/06/2015
<b>Product Name:</b>	500 HYBRID MORTAR B	<b>Supersedes Date:</b>	29/05/2015

**1.2 Relevant identified uses of the substance or mixture and uses advised against**      Component of multicomponent industrial coatings - Industrial use.

**1.3 Details of the supplier of the safety data sheet**

<b>Importer:</b>	StonCor Europe 9 Rue du Travail, 1400 Nivelles, Belgium
<b>Manufacturer:</b>	Stonhard, Division of StonCor Group, Inc. 1000 East Park Avenue Maple Shade, NJ 08052  +1 856 7797500 (US)
	Regulatory /Technical Information: +32 67493710 Nivelles, Belgium +39 02253751 Cologno Monzese, Italy

**Datasheet Produced by:** Darnell, Benjamin - ehs@ stoncor.com

**1.4 Emergency telephone number:** CHEMTREC +1 703 5273887 (Outside US)

## 2 Hazard Identification

**2.1 Classification of the substance or mixture**

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

**HAZARD STATEMENTS**

Hazardous to the aquatic environment, Chronic, category 2	H411
Eye Irritation, category 2	H319
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317

## 2.2 Label elements

### Symbol(s) of Product



### Signal Word

Warning

### Named Chemicals on Label

epoxy resin based on bisphenol F, reaction product bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)

#### HAZARD STATEMENTS

Hazardous to the aquatic environment Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.

#### PRECAUTION PHRASES

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P333+313	IF skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

## 2.3 Other hazards

Not applicable

### Results of PBT and vPvB assessment

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

## 3. Composition/Information On Ingredients

### 3.2 Mixtures

#### Hazardous Ingredients

<u>CAS-No.</u>	<u>EINEC No.</u>	<u>Name According to EEC</u>	<u>%</u>
25068-38-6	500-033-5	reaction product bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)	75-100
100-51-6	202-859-9	benzyl alcohol	10-25
9003-36-5	500-006-8	epoxy resin based on bisphenol F	2.5-10
64742-94-5	265-198-5	solvent naphtha (petroleum), heavy aromatic	0.1-1.0
64742-95-6	265-199-0	solvent naphtha (petroleum), light arom.	0.1-1.0
108-83-8	203-620-1	2,6-dimethylheptan-4-one	0.1-1.0
138-86-3	205-341-0	dipentene	<0.1
97-64-3	202-598-0	ethyl lactate	<0.1

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
25068-38-6	01-2119456619-26-0029	GHS07-GHS09	H315-317-319-411	
100-51-6		GHS07	H302-319-332	
9003-36-5	01-2119454392-40-0007	GHS07-GHS09	H315-317-319-411	
64742-94-5		GHS08	H304	
64742-95-6		GHS02-GHS08-GHS09	H226-304-411	
108-83-8		GHS02-GHS07	H226-335	
138-86-3		GHS02-GHS07-GHS09	H226-315-317-400-410	
97-64-3		GHS02-GHS05-GHS07	H226-318-335	

**Additional Information:** The text for CLP Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

### 4.1 Description of First Aid Measures

**GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice.

**AFTER INHALATION:** Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Prolonged or repeated exposure increases the risk. Harmful to aquatic organisms.

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

## 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above.

### 5.2 Special hazards arising from the substance or mixture

No Information

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

## 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term

adverse effects in the aquatic environment

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /national regulations (see section 13).

### 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Extremes of temperature and direct sunlight

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight

### 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (IR)

Name	%	LTCL ppm	STEL ppm	STEL mg/m3	LTCL mg/m3	OEL Note
reaction product: bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)	75-100					
benzyl alcohol	10-25					
epoxy resin based on bisphenol F	2.5-10					
solvent naphtha (petroleum), heavy aromatic	0.1-1.0					
solvent naphtha (petroleum), light arom.	0.1-1.0					
2,6-dimethylheptan-4-one	0.1-1.0	25			150	
dipentene	<0.1					
ethyl lactate	<0.1					

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified at the EU level under the dangerous substances and preparations regulation.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required.

**EYE PROTECTION:** Safety glasses.

**HAND PROTECTION:** Rubber or plastic gloves. Remove and wash contaminated clothing before re-use.

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. MECHANICAL VENTILATION RECOMMENDED.

**Chemical Name:**

reaction product bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight &lt;= 700)

**EC No.:**

500-033-5

**CAS-No.:**

25068-38-6

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					0.75 mg/kg		0.75 mg/kg
Inhalation		12.25 mg/m <sup>3</sup>		12.25 mg/m <sup>3</sup>				
Dermal		8.33 mg/kg		8.33 mg/kg		3.571 mg/kg		3.571 mg/kg

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	0.006 mg/l
Fresh water sediments	0.996 mg/l
Marine water	0.0006 mg/l
Marine sediments	0.0996 mg/l
Food chain	
Microorganisms in sewage treatment soil (agricultural)	10 mg/l
Air	0.196 mg/kg

**9. Physical and Chemical Properties****9.1 Information on basic physical and chemical properties**

<b>Appearance:</b>	WHITE
<b>Physical State</b>	LIQUID
<b>Odor</b>	NOT DETERMINED
<b>Odor threshold</b>	Not determined
<b>pH</b>	NOT APPLICABLE
<b>Melting point /freezing point (°C)</b>	Not determined
<b>Boiling point/range (°C)</b>	138 - N.D.
<b>Flash Point, (°C)</b>	94
<b>Evaporation rate</b>	Not determined
<b>Flammability (solid, gas)</b>	Not determined
<b>Upper/lower flammability or explosive limits</b>	Not determined
<b>Vapour Pressure</b>	NOT DETERMINED
<b>Vapour density</b>	NOT DETERMINED
<b>Relative density</b>	Not determined
<b>Solubility in /Miscibility with water</b>	NIL
<b>Partition coefficient: n-octanol/water</b>	Not determined
<b>Auto-ignition temperature (°C)</b>	Not determined
<b>Decomposition temperature (°C)</b>	Not determined
<b>Viscosity</b>	620 CPS
<b>Explosive properties</b>	

Oxidising properties Not determined  
Not determined

**9.2 Other information**

VOC Content g/l: 20  
Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.  
Specific Gravity (g/cm<sup>3</sup>) 1.135

## 10. Stability and Reactivity

**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

**10.2 Chemical stability**

No decomposition if stored and applied as directed. Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation does not occur.

**10.4 Conditions to avoid**

Extremes of temperature and direct sunlight

**10.5 Incompatible materials**

Strong oxidizing agents. Acids and bases.

**10.6 Hazardous decomposition products**

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## 11. Toxicological Information

**11.1 Information on toxicological effects****Acute Toxicity:**

Oral LD50:

Inhalation LC50:

**Irritation:** No information available.

**Corrosivity:** No information available.

**Sensitization:** No information available.

**Repeated dose toxicity:** No information available.

**Carcinogenicity:** No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

**STOT-single exposure:** No information available.

**STOT-repeated exposure:** No information available.

**Aspiration hazard:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.  
Data on individual components are tabulated below.

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
25068-38-6	reaction product bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)	>2000 mg/kg, rat, oral	>2000 mg/kg, rat	
100-51-6	benzyl alcohol	1620 mg/kg Rat Oral		>4178 mg/m <sup>3</sup> Rat Inhalation
64742-95-6	solvent naphtha (petroleum), light arom.	4700 mg/kg, oral, rat	>2000 mg/kg	3670 ppm/8 hours, rat, inhalation
108-83-8	2,6-dimethylheptan-4-one	3200 mg/kg, oral, rat		1979 ppm /6 hrs, rat, inhalation

**Additional Information:**

No Information

## 12 Ecological Information

**12.1 Toxicity:**

<b>EC50 48hr (Daphnia):</b>	No information
<b>IC50 72hr (Algae):</b>	No information
<b>LC50 96hr (fish):</b>	No information

**12.2 Persistence and degradability:** No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

**12.5 Results of PBT and vPvB assessment** The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

**12.6 Other adverse effects:** No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
25068-38-6	reaction product bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)	No information	No information	1.5-7.7 mg/L
100-51-6	benzyl alcohol	230 mg/l	700 mg/l	460 mg/l
9003-36-5	epoxy resin based on bisphenol F	No information	No information	
64742-94-5	solvent naphtha (petroleum), heavy aromatic	No information	No information	
64742-95-6	solvent naphtha (petroleum), light arom.	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l
108-83-8	2,6-dimethylheptan-4-one	No information	No information	
138-86-3	dipentene	No information	No information	
97-64-3	ethyl lactate	No information	No information	

**Further Ecological Information**

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

<u>CAS-No.</u>	<u>Name According to EEC</u>
25068-38-6	reaction product bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)
9003-36-5	epoxy resin based on bisphenol F

### 13. Disposal Considerations

- 13.1 WASTE TREATMENT METHODS:** If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 080111  
Packaging Waste Code: 150110

### 14. Transport Information

- |   |  |
|---|--|
| 14.1 UN number  | UN3082   |
| 14.2 UN proper shipping name  | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S |
| Technical name  | DIGLYCIDYL ETHER OF BISPHENOL A                    |
| 14.3 Transport hazard class(es)   | 9  |
| Subsidiary shipping hazard  |  |
| 14.4 Packing group  | III  |
| 14.5 Environmental hazards  |  |
| 14.6 Special precautions for user   | Not applicable                                     |
| EmS-No.:  | F-A, S-F   |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code | Not applicable                                     |

### 15. Regulatory Information

- 15.1 Safety, health and environmental regulations/legislation for the substance or mixture:**

National Regulations:

Denmark Product Registration Number:

Danish MAL Code:

Sweden Product Registration Number:

Norway Product Registration Number:

WGK Class:

**Chemical Safety Assessment**

- 15.2** No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### 16. Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.



H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Reasons for revision

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

#### List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark  
 ESIS (The European Chemical Substances Information System), provided by the European Commission Joint Research Centre in Ispra, Italy  
 Annex VI of the EU Council Directive 67/548/EEC  
 Council Directive 67/548/EEC - Annex I or EU Council Directive 1999/45/EC  
 European Union (EU) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation)  
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

#### Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m <sup>3</sup>	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code

IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.