



**Safety Data Sheet**  
**according to Regulation (EC)**  
**No. 2015/830**

**SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking**

<b>1.1 Product Identifier</b>	04020/B	<b>Revision Date:</b>	23/05/2018
<b>Product Name:</b>	STONPROOF CT5 PART B	<b>Supersedes Date:</b>	22/05/2018

**1.2 Relevant identified uses of the substance or mixture and uses advised against**      Base component of 2 components coating - Industrial use.

**1.3 Details of the supplier of the safety data sheet**

**Importer:**                      StonCor Europe  
 9, Rue du Travail - 1400 Nivelles, Belgium

**Manufacturer:**                Stonhard, Division of StonCor Group, Inc.  
 1000 East Park Avenue  
 Maple Shade, NJ 08052

+1 856 7797500 (US)

Regulatory / Technical Information:  
 +32 67493710 Nivelles, Belgium

**Datasheet Produced by:**      ehs@stonhard.com

**1.4 Emergency telephone number:**      CHEMTREC +1 703 5273887 (Outside US)

**SECTION 2: Hazard Identification**

**2.1 Classification of the substance or mixture**

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

**HAZARD STATEMENTS**

Other EU extensions	EUH205
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Eye Irritation, category 2	H319
STOT, single exposure, category 3, RTI	H335
Germ Cell Mutagenicity, category 2	H341

Hazardous to the aquatic environment, Chronic, category 2

H411

**2.2 Label elements****Symbol(s) of Product****Signal Word**

Warning

**Named Chemicals on Label**

2,3-epoxypropyl o-tolyl ether, polypropyleneglycol glycidyl ether, Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), anhydrous aluminum silicate

**HAZARD STATEMENTS**

Other EU extensions	EUH205	Contains epoxy constituents. May produce an allergic reaction.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Germ Cell Mutagenicity, category 2	H341	Suspected of causing genetic defects.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

**PRECAUTION PHRASES**

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.
P405	Store locked up.

**2.3 Other hazards**

No Information

**Results of PBT and vPvB assessment:**

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**SECTION 3: Composition/Information On Ingredients****3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>EINEC No.</u>	<u>Name According to EEC</u>	<u>%</u>
25068-38-6	500-033-5	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25-50

9072-62-2	618-635-2	polypropyleneglycol glycidyl ether	10-25
2210-79-9	218-645-3	2,3-epoxypropyl o-tolyl ether	10-25
66402-68-4	266-340-9	anhydrous aluminum silicate	10-25
13463-67-7	236-675-5	titanium dioxide	2.5-10
21645-51-2	244-492-7	alumina trihydrate	0.1-1.0
64742-94-5	265-198-5	Solvent naphtha (petroleum), heavy arom.	0.1-1.0

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
25068-38-6	01-2119456619-26	GHS07-GHS09	H315-317-319-335-411	
9072-62-2		GHS07	H315-317-319	
2210-79-9		GHS07-GHS08-GHS09	H315-317-341-411	
66402-68-4		GHS07	H315-319-335	
13463-67-7	01-2119489379-17			
21645-51-2	01-2119529246-39			
64742-94-5		GHS08	H304	

**Remarks:** CAS No. 25068-38-6 identified as CAS No. 1675-54-3, EC No. 216-823-5 under REACH Registration

**Additional Information:** The text for CLP Hazard Statements shown above (if any) is given in Section 16.

## SECTION 4: First-aid Measures

### 4.1 Description of First Aid Measures

**GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice.

**AFTER INHALATION:** Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

#### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Prolonged or repeated exposure increases the risk. Harmful to aquatic organisms.

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

## SECTION 5: Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above.

### 5.2 Special hazards arising from the substance or mixture

No Information

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

## SECTION 6: Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## SECTION 7: Handling and Storage

### 7.1 Precautions for safe handling

Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Extremes of temperature and direct sunlight.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

No specific advice for end use available.

## SECTION 8: Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (IR)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6				
polypropyleneglycol glycidyl ether	9072-62-2				
2,3-epoxypropyl o-tolyl ether	2210-79-9				
anhydrous aluminum silicate	66402-68-4				
titanium dioxide	13463-67-7				4, 10
alumina trihydrate	21645-51-2				
Solvent naphtha (petroleum), heavy arom.	64742-94-5				

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required.

**EYE PROTECTION:** Safety glasses.

**HAND PROTECTION:** Impervious gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use.

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

**Chemical Name:**

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

**EC No.:**  
500-033-5

**CAS-No.:**  
25068-38-6

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					0.75 mg/kg		0.75 mg/kg
Inhalation		12.25 mg/m <sup>3</sup>		12.25 mg/m <sup>3</sup>				
Dermal		8.33 mg/kg		8.33 mg/kg		3.571 mg/kg		3.571 mg/kg

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	0.006 mg/l
Fresh water sediments	0.996 mg/l
Marine water	0.0006 mg/l
Marine sediments	0.0996 mg/l
Food chain	
Microorganisms in sewage treatment	10 mg/l
soil (agricultural)	0.196 mg/kg
Air	

**Chemical Name:**

titanium dioxide

**EC No.:**  
236-675-5

**CAS-No.:**  
13463-67-7

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							700 mg/kg/d
Inhalation			10					
Dermal								

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	0.127
Fresh water sediments	1000
Marine water	1
Marine sediments	100
Food chain	1667
Microorganisms in sewage treatment	100 mg/l
soil (agricultural)	100
Air	

**SECTION 9: Physical and Chemical Properties****9.1 Information on basic physical and chemical properties**

**Appearance:** Gray

**Physical State** LIQUID

**Odor** Faint epoxy

<b>Odor threshold</b>	Not determined
<b>pH</b>	Non-aqueous
<b>Melting point / freezing point (°C)</b>	Not determined
<b>Boiling point/range (°C)</b>	111 - N.D.
<b>Flash Point, (°C)</b>	94
<b>Evaporation rate</b>	Not determined
<b>Flammability (solid, gas)</b>	Not determined
<b>Upper/lower flammability or explosive limits</b>	Not determined
<b>Vapour Pressure</b>	Not determined
<b>Vapour density</b>	Not determined
<b>Relative density</b>	Not determined
<b>Solubility in / Miscibility with water</b>	Negligible
<b>Partition coefficient: n-octanol/water</b>	Not determined
<b>Auto-ignition temperature (°C)</b>	Not determined
<b>Decomposition temperature (°C)</b>	Not determined
<b>Viscosity</b>	12-16000 cps
<b>Explosive properties</b>	Not applicable
<b>Oxidising properties</b>	Not applicable

## 9.2 Other information

<b>VOC Content g/l:</b>	5
<b>Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.</b>	
<b>Specific Gravity (g/cm<sup>3</sup>)</b>	1.334

## SECTION 10: Stability and Reactivity

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

### 10.2 Chemical stability

No decomposition if stored and applied as directed. Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Extremes of temperature and direct sunlight.

### 10.5 Incompatible materials

Strong oxidizing agents. Acids and bases.

### 10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## SECTION 11: Toxicological Information

### 11.1 Information on toxicological effects

**Acute Toxicity:**

<b>Oral LD50:</b>	No Information
<b>Inhalation LC50:</b>	No Information
<b>Irritation:</b>	No information available.
<b>Corrosivity:</b>	No information available.
<b>Sensitization:</b>	No information available.
<b>Repeated dose toxicity:</b>	No information available.
<b>Carcinogenicity:</b>	No information available.
<b>Mutagenicity:</b>	No information available.
<b>Toxicity for reproduction:</b>	No information available.
<b>STOT-single exposure:</b>	No information available.
<b>STOT-repeated exposure:</b>	No information available.
<b>Aspiration hazard:</b>	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	>2000 mg/kg, rat, oral	>2000 mg/kg, rat	
2210-79-9	2,3-epoxypropyl o-tolyl ether	5800 mg/kg, oral, rat		1220 ppm/4 hr
13463-67-7	titanium dioxide	10000 mg/kg, oral (rat)		

#### Additional Information:

This product is classified as a "Reproductive Toxicity - Category 2" due to containing a substance classified as a reproductive toxin via ingestion / oral exposure route only. Normal product application methods by trained crew members would not present a risk of oral exposure or ingestion. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

## SECTION 12: Ecological Information

### 12.1 Toxicity:

<b>EC50 48hr (Daphnia):</b>	No information
<b>IC50 72hr (Algae):</b>	No information
<b>LC50 96hr (fish):</b>	No information

**12.2 Persistence and degradability:** No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

**12.5 Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	1.8 mg/l	No information	1.5-7.7 mg/L
9072-62-2	polypropyleneglycol glycidyl ether	No information	No information	
2210-79-9	2,3-epoxypropyl o-tolyl ether	No information	No information	
66402-68-4	anhydrous aluminum silicate	No information	No information	
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
21645-51-2	alumina trihydrate	No information	No information	
64742-94-5	Solvent naphtha (petroleum), heavy arom.	No information	No information	

### SECTION 13: Disposal Considerations

13.1 **WASTE TREATMENT METHODS:** If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 080111  
Packaging Waste Code: 150110

### SECTION 14: Transport Information

14.1 UN number	UN3082
14.2 UN proper shipping name	Environmentally Hazardous Substance, Liquid, n.o.s.
Technical name	Reaction products: bisphenol-A-(Epichlorohydrin) epoxy resin
14.3 Transport hazard class(es)	9
Subsidiary shipping hazard	N/A
14.4 Packing group	III
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	Not applicable
EmS-No.:	F-A, S-F
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

### SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

**National Regulations:**

Denmark Product Registration Number: 1914876  
Danish MAL Code: 00-5 (1993)  
Danish MAL Code - Mixture: Not available  
Sweden Product Registration Number: Not available  
Norway Product Registration Number:



Not available

**Germany WGK Class:**

Not available

**Covered by Directive 2012/18/EC (Seveso III):**

Not applicable

**Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:**

Not applicable

**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

**SECTION 16: Other Information****Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.

**Reasons for revision**

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

**List of References:**

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;  
 European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;  
 European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);  
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

**Acronym & Abbreviation Key:**

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals

LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

