



Safety Data Sheet
according to Regulation (EC)
No. 2015/830



SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	11295...	Revision Date:	09/03/2018
Product Name:	CARBOCRYLIC 1295 HS -PART A	Supersedes Date:	07/11/2016
		Version Number:	1
1.2 Relevant identified uses of the substance or mixture and uses advised against	Advised against: Please see Technical Data Sheet. Base component of 2 components coating - Industrial use.		
Product to be mixed with:	CARBOCRYLIC 1295 HS - B		
Mixing ratio by volume Part A/ Part B:	7 / 1		
1.3 Details of the supplier of the safety data sheet			
Importer:	StonCor Europe 9, Rue du Travail - 1400 Nivelles, Belgium		
Manufacturer:	Carboline Italia, S.p.a. Via Margherita Vigano' De Vizzi . n 77 20092 Cinisello Balsamo (MI) Italy		
	Regulatory / Technical Information: +32 67493710 Nivelles, Belgium +39 02253751 Cinisello Balsamo, Italy		
Datasheet Produced by:	Solvesi, Anna - ehs@stoncor.com		
1.4 Emergency telephone number:	CHEMTREC +1 703 5273887 (Outside US) PPC +1 412 6816669 (Outside US) Centro Antiveleni di Roma +39 06 49978000 (CAV) Policlinico Umberto I - Roma)(24h/24h) Emergenza ambientale +39 335-601 32 88 / +39 347-949 84 88 / +39 348-246 90 99		

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 3	H226
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Serious Eye Damage, category 1	H318

STOT, repeated exposure, category 2
 Hazardous to the aquatic environment, Chronic, category 3

H373

H412

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Butan-1-ol, Ethylbenzene, toluene, Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate, xylene

HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

PRECAUTION PHRASES

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P242	Use only non-sparking tools.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P362+364	Take off contaminated clothing and wash it before reuse.

ADDITIONAL INFORMATION

**	Note P : The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
ADD-01	The product contains max 0.01% benzen.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

SECTION 3: Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.	EINEC No.	Name According to EEC	%
13463-67-7	236-675-5	titanium dioxide	10-25
1330-20-7	215-535-7	xylene	10-25
123-86-4	204-658-1	n-butyl acetate	2.5-10

71-36-3	200-751-6	Butan-1-ol	2.5-10
100-41-4	202-849-4	Ethylbenzene	2.5-10
	918-668-5	hydrocarbons, c9, aromatics**	1.0-2.5
67-63-0	200-661-7	Propan-2-ol	1.0-2.5
67762-90-7	614-122-2	Siloxanes and Silicones, di-Me, reaction products with silica	1.0-2.5
	915-687-0	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	0.1-1.0
108-88-3	203-625-9	toluene	0.1-1.0
141-32-2	205-480-7	n-Butyl acrylate	0.1-1.0
		E96096 (01-0000018057-71)	0.1-1.0

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
13463-67-7	01-2119489379-17			
1330-20-7	01-2119488216-32	GHS02-GHS07-GHS08	H226-304-312-315-319-332-335-373	
123-86-4	01-2119485493-29	GHS02-GHS07	H226-336	
71-36-3	01-2119484630-38	GHS02-GHS05-GHS07	H226-302-315-318-335-336	
100-41-4	01-2119489370-35	GHS02-GHS07-GHS08	H225-304-332-373-412	
	01-2119455851-35	GHS02-GHS07-GHS08-GHS09	H226-304-335-336-411	
67-63-0	01-2119457558-25	GHS02-GHS07	H225-319-336	
67762-90-7				
	01-2119491304-40	GHS07-GHS09	H317-400-410	
108-88-3	01-2119471310-51	GHS02-GHS07-GHS08	H225-304-315-336-361d-373-412	
141-32-2	01-2119453155-43	GHS02-GHS07	H226-315-317-319-332-335-412	
		GHS07	H317-413	

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Provide fresh air, rest and warmth. Call a physician immediately. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes. Irritating to respiratory system. Irritating to skin. Risk of serious damage to eyes. May cause sensitization by skin contact. Danger of serious damage to health by prolonged exposure. Harmful by inhalation and in contact with skin. Irritating to eyes and skin. Irritating to eyes, respiratory system and skin. Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11. When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

SECTION 6: Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage**7.1 Precautions for safe handling**

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store away from: oxidising materials, acids, and alkalis. Store in upright position only. Storage of flammable liquids.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure Controls/Personal Protection**8.1 Control parameters****Ingredients with Occupational Exposure Limits****(UK WELS)**

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
titanium dioxide	13463-67-7			10 (total dust)	4 (resp. dust)
xylene	1330-20-7	50	100	441	220
n-butyl acetate	123-86-4	150	200	966	724
Butan-1-ol	71-36-3		50	154	
Ethylbenzene	100-41-4	100	125	552	441
hydrocarbons, c9, aromatics**					100
Propan-2-ol	67-63-0	400	500	1250	999

Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7			6 (Inh. dust)	2.4 (Resp. dust)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate					
toluene	108-88-3	50	100	384	191
n-Butyl acrylate	141-32-2	1	5	26	5
E96096 (01-0000018057-71)					

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
titanium dioxide	13463-67-7	
xylene	1330-20-7	Sk
n-butyl acetate	123-86-4	
Butan-1-ol	71-36-3	Sk
Ethylbenzene	100-41-4	Can be absorbed through the skin.
hydrocarbons, c9, aromatics**		
Propan-2-ol	67-63-0	
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
toluene	108-88-3	Sk
n-Butyl acrylate	141-32-2	
E96096 (01-0000018057-71)		

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required. Use compressed air or fresh air breathing apparatus in closed compartments. Wear respiratory protection with combination filter (dust and gas filter, EN 141) during spraying operations: Gas filter type A1 (organic substances). Dust filter P3 (for fine dust).

EYE PROTECTION: If splashes are likely to occur, wear: Face-shield, tightly fitting safety goggles.

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Nitrile rubber. Butyl rubber. Viton®. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

Chemical Name:

titanium dioxide

EC No.:

236-675-5

CAS-No.:

13463-67-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							700 mg/kg/ bw/ day
Inhalation			10 mg/m ³				10 mg/m ³	
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.127 mg/L
Fresh water sediments	1000 mg/kg dw
Marine water	1 mg/L
Marine sediments	100 mg/kg dw
Food chain	1667 mg/kg (oral)
Microorganisms in sewage treatment	100 mg/kg
soil (agricultural)	100 mg/kg dw
Air	

Chemical Name:

xylene

EC No.:

215-535-7

CAS-No.:

1330-20-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.6 mg/kg bw/ day
Inhalation	289 mg/m ³	289 mg/m ³		77 mg/m ³	174 mg/m ³	174 mg/m ³		14.8 mg/m ³
Dermal				180 mg/kg bw/ day				108 mg/kg bw/ day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/L
soil (agricultural)	2.31 mg/kg
Air	

Chemical Name:

n-butyl acetate

EC No.:

204-658-1

CAS-No.:

123-86-4

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					2 mg/kg bw/day - neurotoxicity-		2 mg/kg bw/day -neurotoxicity-
Inhalation	300 mg/m ³ (irritation (respiratory tract))	600 mg/m ³	300 mg/m ³	48 mg/m ³	300 mg/m ³ (irritation (respiratory tract))	300 mg/m ³ (irritation (respiratory tract))	35.7 mg/m ³ (irritation (respiratory tract))	12 mg/m ³
Dermal		11 mg/kg bw/day - neurotoxicity-		7 mg/kg bw/day	No hazard identified	6 mg/kg bw/day - neurotoxicity		3.4 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.18 mg/l
Fresh water sediments	0.981 mg/kg
Marine water	0.018 mg/l
Marine sediments	0.0981 mg/kg
Food chain	
Microorganisms in sewage treatment	35.6 mg/L
soil (agricultural)	0.0903 mg/kg
Air	

Chemical Name:

Butan-1-ol

EC No.:

200-751-6

CAS-No.:

71-36-3

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							3,1 mg/kg bw/day
Inhalation			310 mg/m ³				55 mg/m ³	
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0,082 mg/l
Fresh water sediments	0,178 mg/kg dw
Marine water	0,0082 mg/l
Marine sediments	0,0178 mg/kg dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	0,015 mg/kg dw
Air	

Chemical Name:

Ethylbenzene

EC No.:

202-849-4

CAS-No.:

100-41-4

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.6 mg/kg bw/day
Inhalation	293 mg/m ³ irritation (respiratory tract)	Low hazard (no threshold derived)		77 mg/m ³		Low hazard (no threshold derived)		15 mg/m ³
Dermal				180 mg/kg bw/day				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	100 µg/L
Fresh water sediments	13.7 mg/kg sediment dw
Marine water	10 - 100 µg/L
Marine sediments	1.37 mg/kg sediment dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	2.68 mg/kg soil dw
Air	

Chemical Name:

hydrocarbons, c9, aromatics**

EC No.:

918-668-5

CAS-No.:**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							11 mg/kg bw/day
Inhalation				150 mg/m ³				32 mg/m ³
Dermal				25 mg/kg bw/day				11 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

Chemical Name:

Propan-2-ol

EC No.:

200-661-7

CAS-No.:

67-63-0

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required						26 mg/kg	
Inhalation				500 mg/m ³				89 mg/m ³
Dermal				888 mg/kg				319 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	140.9 mg/l
Fresh water sediments	552 mg/kg
Marine water	140.9 mg/l
Marine sediments	552 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	28 mg/kg
Air	

Chemical Name:

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

EC No.:

915-687-0

CAS-No.:**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					1.25 mg/kg		1.25 mg/kg
Inhalation		2.35 mg/m ³		2.35 mg/m ³		0.58 mg/m ³		0.58 mg/m ³
Dermal		2.5 mg/kg		2.5 mg/kg		1.25 mg/kg		1.25 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.0022 mg/l
Fresh water sediments	1.05 mg/kg
Marine water	0.00022 mg/l
Marine sediments	0.11 mg/kg
Food chain	
Microorganisms in sewage treatment	1 mg/l (as sewage treatment)
soil (agricultural)	0.21 mg/kg
Air	

Chemical Name:

toluene

EC No.:

203-625-9

CAS-No.:

108-88-3

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							8.13 mg/kg bw/day
Inhalation	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3	226 mg/m3	226 mg/m3	56.5 mg/m3	56.5 mg/m3
Dermal				384 mg/Kg bw/day				226 mg/Kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.68 mg/l
Fresh water sediments	16.39 mg/kg
Marine water	0.68 mg/l
Marine sediments	16.39 mg/kg
Food chain	
Microorganisms in sewage treatment	13.61 mg/l
soil (agricultural)	2.89 mg/kg
Air	

Chemical Name:

E96096 (01-0000018057-71)

EC No.:**CAS-No.:****DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							
Inhalation		18 mg/m3	3 mg/m3					
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0,0368 mg/l
Fresh water sediments	1456 mg/kg dw (sediment)
Marine water	0,00368 mg/l
Marine sediments	
Food chain	
Microorganisms in sewage treatment	10 mg/l (sewage treatment)
soil (agricultural)	103906 mg/kg dw
Air	

SECTION 9: Physical and Chemical Properties**9.1 Information on basic physical and chemical properties**

Appearance:	Various colors
Physical State	LIQUID
Odor	solvent
Odor threshold	Not determined
pH	Not applicable
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	106 - 143

Flash Point, (°C)	26
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	Not determined
Vapour Pressure	Not determined
Vapour density	>1 (air = 1)
Relative density	1.36
Solubility in / Miscibility with water	PARTIALLY
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	>370
Decomposition temperature (°C)	Not determined
Viscosity	95 - 105 KU
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	340
Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.	
Specific Gravity (g/cm ³)	1.34

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Stable under normal conditions.

10.3 Possibility of hazardous reactions

No reactivity hazards known under recommended storage and use conditions. No reactivity hazards known under normal storage and use conditions.

10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources.

10.5 Incompatible materials

Acids. Strong oxidizing agents. Keep away from strong oxidising agents and strongly acid or alkaline materials.

10.6 Hazardous decomposition products

In case of fire **hazardous decomposition products** may be produced such as: Carbon monoxide (CO), carbon dioxide (CO₂), oxides of nitrogen (NO_x).

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available on the product itself as the product is not tested.

Inhalation LC50: No information available on the product itself as the product is not tested.

Irritation: Irritant

Corrosivity: Causes serious eye damage.

Sensitization:	No information available.
Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
13463-67-7	titanium dioxide	>5000 mg/kg (oral-rat)	10000	
1330-20-7	xylene	>2000 mg/kg, rat, oral	3200 mg/kg, rabbit, dermal	11 mg/L (ATE inh/vapour)
123-86-4	n-butyl acetate	10760 mg/kg, rat, oral	14112 mg/Kg (rabbit)	23.4 mg/l/4/h (rat)
71-36-3	Butan-1-ol	790 mg/kg rat, oral	3400 mg/kg, rabbit	8000 mg/l 4hrs rat, inhalation
100-41-4	Ethylbenzene	3500 mg/kg rat, oral	>20000 mg/kg bw (rabbit)	
	hydrocarbons, c9, aromatics**	3592 mg/kg	> 3160 mg/kg	> 6193 mg/m3
67-63-0	Propan-2-ol	4720 mg/kg rat, oral		22500 ppm/8hrs rat, inhalation
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	6350 mg/kg, oral, rat		
108-88-3	toluene	5000 mg/kg rat oral	14000 mg/kg rabbit	8000 ppm/4hrs, rat, inhalation
141-32-2	n-Butyl acrylate	3143 mg/Kg (Oral, rabbit)	>2000 mg/Kg (Dermal, rabbit, 2000-3024 mg/kg)	10.3 mg/l (inhalation vapor, rat, 4h)
	E96096 (01-0000018057-71)	No death: 4 h/Ratto:4,1 mg/l	No death: 2.000 mg/kg (oral, rat)	No death: 2.000 mg/kg (oral, rat)

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Respiration of solvent vapour may cause dizziness. Repeated and prolonged exposure to solvents may cause brain and nervous system damage. Chronic exposure causes drying effect on the skin and eczema. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes. CNS depressant. Inhalation is the main hazard in industrial use. The solvent vapours can be harmful and cause headaches, nausea, and intoxication. Acts as a defatting agent on skin. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential:	No information
12.4 Mobility in soil:	No information
12.5 Results of PBT and vPvB assessment:	The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.
12.6 Other adverse effects:	No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)	16 mg/l (EC50, 72h, Pseudokirchnerella subcapitata)	>100 mg/l (EC50, 96h, Oncorhynchus Mykiss OECD203)
1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/L (Selenastrum sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrochirus), 21.0 mg/L (Pimephales promelas)
123-86-4	n-butyl acetate	No information	No information	18 mg/L (Pimephales promelas)
71-36-3	Butan-1-ol	No information	No information	1740 mg/l (Pimephales promelas)
100-41-4	Ethylbenzene	No information	No information	5.1 mg/L (Atlantic silverfish)
	hydrocarbons, c9, aromatics**	3,2 mg/l (Daphnia Magna)	No information	No information
67-63-0	Propan-2-ol	No information	No information	4200 mg/L (fish)
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	No information	No information	
	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No information	No information	0.97 mg/L (Lepomis macrochirus)
108-88-3	toluene	No information	No information	5.5 mg/l (Oncorhynchus kisutch)
141-32-2	n-Butyl acrylate	8.2 mg/L (Daphnia magna)	2.65 mg/L; 5.9 mg/L (Pseudokirchneriella subcapitata)	2.1 mg/L (Cyprinus carpio); 5.2 mg/L (Oncorhynchus mykiss)
	E96096 (01-0000018057-71)	> 100 mg/l (daphnia magna, 48h, EC50)	> 100 mg/l (CE50, 72 h Pseudokirchneriella subcapitata)	No information

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

European Waste Code: 08 01 11*
Packaging Waste Code: 15 01 10

SECTION 14: Transport Information

14.1	UN number	UN1263
14.2	UN proper shipping name	' PAINT
	Technical name	Not applicable
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	Not applicable
14.4	Packing group	III
14.5	Environmental hazards	Marine pollutant: No
14.6	Special precautions for user	Not applicable
	EmS-No.:	F-E, <u>S-E</u>
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

SECTION 15: Regulatory Information**15.1 Safety, health and environmental regulations/legislation for the substance or mixture:****National Regulations:**

Denmark Product Registration Number:	Not available
Danish MAL Code:	Not available
Danish MAL Code - Mixture:	Not available
Sweden Product Registration Number:	Not available
Norway Product Registration Number:	Not available
Germany WGK Class:	2
Directive 2004/42/CE :	450 g/l (subcat j)
Covered by Directive 2012/18/EC (Seveso III):	P5c
Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:	CAS 108-88-3 point 48; Mix: points 3, 40

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information**Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

14 - Transportation Information

15 - Regulatory Information

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes. This safety data sheet (SDS) applies to several colours and is based on the colour with the most stringent classification. Thus, for some colours, there may be a different classification than the one given in section 2.2 in this SDS.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;

European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);

EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community

ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

