



Safety Data Sheet
according to Regulation (EC)
No. 2015/830



SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

- | | | | |
|-------------------------------|---------------------------|-------------------------|----------------|
| 1.1 Product Identifier | TE10200F | Revision Date: | 20/04/2017 |
| Product Name: | THERMALINE 200 FINISH ALU | Supersedes Date: | 03/06/2015 |
| | | Version Number: | No Information |
- 1.2 Relevant identified uses of the substance or mixture and uses advised against** Monocomponent industrial coating - Industrial use.
- 1.3 Details of the supplier of the safety data sheet**
- Importer:** StonCor Europe
9, Rue du Travail - 1400 Nivelles, Belgium
- Manufacturer:** StonCor Europe
9 Rue du Travail
1400 Nivelles
Belgium
- Regulatory / Technical Information:**
+32 67493710 Nivelles, Belgium
- Datasheet Produced by:** Diepstraten, Guus - ehs@stoncor.com
- 1.4 Emergency telephone number:** CHEMTREC +1 703 5273887 (Outside US)
PPC +1 412 6816669 (Outside US)
Centro Antiveleni di Roma +39 06 49978000 (CAV
Policlinico Umberto I - Roma)(24h/24h)
Emergenza ambientale +39 335-601 32 88 / +39
347-949 84 88 / +39 348-246 90 99

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 3	H226
Skin Irritation, category 2	H315
Eye Irritation, category 2	H319
STOT, single exposure, category 3, RTI	H335
STOT, single exposure, category 3, NE	H336
STOT, repeated exposure, category 1	H372

Hazardous to the aquatic environment, Chronic, category 2

H411

2.2 Label elements**Symbol(s) of Product****Signal Word**

Danger

Named Chemicals on Label

Butan-1-ol, xylene, Naphtha (petroleum), hydrodesulfurized heavy, Solvent naphtha (petroleum), light arom.

HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

No information

SECTION 3: Composition/Information On Ingredients**3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>EINEC No.</u>	<u>Name According to EEC</u>	<u>%</u>
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom.	10-25
64742-82-1	265-185-4	Naphtha (petroleum), hydrodesulfurized heavy	10-25

1330-20-7	215-535-7	xylene	10-25
71-36-3	200-751-6	Butan-1-ol	2.5-10
95-63-6	202-436-9	1,2,4-trimethylbenzene	0.1-1.0
64742-49-0	265-151-9	Naphtha (petroleum), hydrotreated light	0.1-1.0
108-67-8	203-604-4	Mesitylene	0.1-1.0

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
64742-95-6	01-2119455851-35	GHS02-GHS07-GHS08-GHS09	H226-304-335-336-411	
64742-82-1	01-2119458049-33	GHS02-GHS07-GHS08-GHS09	H226-304-336-372-411	
1330-20-7	01-2119488216-32	GHS02-GHS07-GHS08	H226-304-312-315-319-332-335-373	
71-36-3	01-2119484630-38	GHS02-GHS05-GHS07	H226-302-315-318-335-336	
95-63-6	01-2119472135-42	GHS02-GHS07-GHS09	H226-315-319-332-335-411	
108-67-8	01-2119463878-19	GHS02-GHS07-GHS08-GHS09	H226-304-315-319-335-411	
64742-49-0		GHS02-GHS07-GHS08-GHS09	H225-302-304-411	

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
Solvent naphtha (petroleum), light arom.	64742-95-6				
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1				
xylene	1330-20-7	50	100	442	221
Butan-1-ol	71-36-3				
1,2,4-trimethylbenzene	95-63-6	20			100
Naphtha (petroleum), hydrotreated light	64742-49-0				
Mesitylene	108-67-8	20			100

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
Solvent naphtha (petroleum), light arom.	64742-95-6	
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	
xylene	1330-20-7	Sk
Butan-1-ol	71-36-3	Sk
1,2,4-trimethylbenzene	95-63-6	
Mesitylene	108-67-8	
Naphtha (petroleum), hydrotreated light	64742-49-0	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Chemical Name:

Solvent naphtha (petroleum), light arom.

EC No.:
265-199-0

CAS-No.:
64742-95-6

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							11 mg/kg
Inhalation								32 mg/m ³
Dermal								11 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

Chemical Name:

Naphtha (petroleum), hydrodesulfurized heavy

EC No.:
265-185-4

CAS-No.:
64742-82-1

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							26 mg/kg
Inhalation				330 mg/m ³				71 mg/m ³
Dermal				44 mg/kg				26 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

Chemical Name:

xylene

EC No.:

215-535-7

CAS-No.:

1330-20-7

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							1.6 mg/kg bw/day
Inhalation	289 mg/m ³	289 mg/m ³		77 mg/m ³	174 mg/m ³	174 mg/m ³		14.8 mg/m ³
Dermal				180 mg/kg bw/day				108 mg/kg bw/day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/L
soil (agricultural)	2.31 mg/kg
Air	

Chemical Name:

Butan-1-ol

EC No.:

200-751-6

CAS-No.:

71-36-3

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							3,1 mg/kg bw/day
Inhalation			310 mg/m ³				55 mg/m ³	
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0,082 mg/l
Fresh water sediments	0,178 mg/kg dw
Marine water	0,0082 mg/l
Marine sediments	0,0178 mg/kg dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	0,015 mg/kg dw
Air	

SECTION 9: Physical and Chemical Properties**9.1 Information on basic physical and chemical properties**

Appearance:	Fluid
Physical State	LIQUID
Odor	CHARACTERISTIC
Odor threshold	Not determined
pH	N/A
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	137°C - N.D.

Flash Point, (°C)	30
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	0,6 Vol% - 7,5 Vol%
Vapour Pressure	6,7 hPa
Vapour density	NOT DETERMINED
Relative density	Not determined
Solubility in / Miscibility with water	Not miscible or different to mix.
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	450°C, Product is not selfigniting.
Decomposition temperature (°C)	Not determined
Viscosity	50 s (20°C / ISO 6mm)
Explosive properties	Product is not explosive. However, formation of explosive air/vapour
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	471
Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.	
Specific Gravity (g/cm3)	1.11

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No Information

Inhalation LC50: No Information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-95-6	Solvent naphtha (petroleum), light arom.	4700 mg/kg, oral, rat	>2000 mg/kg (dermal-rabbit)	3670 ppm/8 hours, rat, inhalation
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	>5000 mg/kg, rat, oral		
1330-20-7	xylene	>2000 mg/kg, rat, oral	3200 mg/kg, rabbit, dermal	20 mg/L (inh/vapour/rat)
71-36-3	Butan-1-ol	790 mg/kg rat, oral	3400 mg/kg, rabbit	8000 mg/l 4hrs rat, inhalation
95-63-6	1,2,4-trimethylbenzene	6000 mg/kg, oral, rat		18000 mg/m ³ /4hours
64742-49-0	Naphtha (petroleum), hydrotreated light	2000 mg/kg (rat)	4000 mg/kg (rabbit)	54 mg/l (rat)

Additional Information:

No Information

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: No information

12.6 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
64742-95-6	Solvent naphtha (petroleum), light arom.	No information	No information	No information
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	No information	No information	
1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/L (Selenastrum sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrochirus), 21.0 mg/L (Pimephales promelas)
71-36-3	Butan-1-ol	No information	No information	1740 mg/l (Pimephales promelas)

95-63-6	1,2,4-trimethylbenzene	No information	No information	
64742-49-0	Naphtha (petroleum), hydrotreated light	No information	No information	
108-67-8	Mesitylene	No information	No information	No information

Further Ecological Information

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

<u>CAS-No.</u>	<u>Name According to EEC</u>
64742-95-6	Solvent naphtha (petroleum), light arom.
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 080111
Packaging Waste Code: 150110

SECTION 14: Transport Information

14.1 UN number	UN1263
14.2 UN proper shipping name	PAINT
Technical name	PAINT
14.3 Transport hazard class(es)	3
Subsidiary shipping hazard	Not applicable
14.4 Packing group	III
14.5 Environmental hazards	Marine Pollutant : No
14.6 Special precautions for user	Not applicable
EmS-No.:	F-E,S-E
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:	Not available
Danish MAL Code:	Not available
Danish MAL Code - Mixture:	Not available
Sweden Product Registration Number:	Not available
Norway Product Registration Number:	Not available
WGK Class:	2
Directive 2004/42/CE :	Not available

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information**Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

Substance Chemical Name Changed

Substance and/or Product Properties Changed in Section(s):

1. Identification

11 - Toxicological Information

12 - Ecological Information

13 - Disposal Information

14 - Transportation Information

15 - Regulatory Information

2. Hazard Identification

3. Composition/Information On Ingredients

8. Exposure Controls/Personal Protection

Substance Hazard Threshold % Changed

Statement(s) Changed

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;
European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission
Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of
substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);
EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m ³	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration

PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

